

Category IEC / EN:	Type 2 surge protection device (SPD)
Location of use:	Main and sub-distribution boards
Networks:	TN-S and TT
Protection modes:	L-N, N-PE
Impulse current discharge rating :	I_{max} : 40 kA
Complies with:	EN 61643-11, IEC 61643-11
Pluggable module	
Remote signaling (option)	
Optimized to TOV	

Technical data: C PRO 40/275 1+1 & C PRO 40/275 1+1-R (with remote contact)				
Protection mode		L-N		N-PE
System nominal voltage(AC)	U_n	230/400 V(50/60 Hz)		
Max.continuos operating voltage (AC)	U_c	275 Vac		255 Vac
Nominal discharge current (8/20)	I_n		20 kA	
Max. discharge current (8/20)	I_{max}		40 kA	
Voltage protection level at In	U_p	1,5 kV		1,5 kV
Voltage protection level at 5kA	U_{res}	1 kV		1,5 kV
Response time	t_a	< 25 ns		<100 ns
Temporary overvoltage 5 s	U_{TOV}	335 V- whitstand		
Temporary overvoltage 120 min	U_{TOV}	440 V-safe failure		
Temporary overvoltage 1200 V for 200ms	U_{TOV}			whitstand
Short circuit whitstand capability with max.overcurrent protection	I_{SCCR}	50 kArms		
Max.overcurrent protection		125 AgG		
Max.overcurrent protection with V connection	I_L	63 AgG		
Follow current extinguishing capability	I_{fi}			100 A
Operating temperature range	t_a	-40 °C ... +80 °C		
Operating state / fault indication		green / red		
Number of ports		1		
Mechnical characteristics				
Min.cross section for terminals	mm²	1,5 mm² solid wire		
Max.cross section for terminals	mm²	25 mm² flex. Wire/35 mm² solid wire		
Mounting		indoor/35 mm DIN rails acc. to EN 60715		
Enclousure material/flammability rate		thermoplastic, gray, UL 94 V-0		
Degree of protection		IP 20		
Type of remote signalling contact		changeover contact		
Switching capacity (a.c.)		250 V / 0.5 A		
Switching capacity (d.c.)		250 V / 0.1 A; 125 V / 0.2 A; 75 V / 0.5 A		

Order informations	Order Code	Weight
C PRO 40/275 1+1	600037	179 g
C PRO 40/275 1+1-R (with remote contact)	600038	184 g
C PRO 40/275-M (module)	600029	43 g
C PRO N-PE 255-M (module)	600030	30 g



