

■ Modular enclosures - IP66 >> Enclosures with OPTIMA Series cutouts >> M400

DOMINO IP66 Series [enclosure]

672.



2 SOCKETS - 12 DIN



1 SOCKET 63A - 12 DIN



3 SOCKETS - 16 DIN

MODULAR ENCLOSURE

SURFACE MOUNTING

IP66

Modularity	No. Modules	Dimension	Power	672.3300 ^[1] [2]		672.3302 ^[3]		672.4316 ^[2]	
M400	12 MOD.	400x256x140mm	22W		1/6		1/6		
	16 MOD.	400x328x140mm	28W						1/4

[1] Connection device to be fixed in the upper side.

[2] 16A (70x87mm) or, with suitable adaption, 32A socket (84x106mm).

[3] 63A (100x110mm)

- Power dissipation calculated in conformity with CEI 23-49 italian standards

■ Modular enclosures - IP66 >> Enclosures with OPTIMA Series cutouts >> M550

DOMINO IP66 Series [enclosure]

672.



6 SOCKETS - 16 DIN



8 SOCKETS - 24 DIN

MODULAR ENCLOSURE

SURFACE MOUNTING

IP66

Modularity	No. Modules	Dimension	Power	672.5616		672.5822		672.5822.1102 ^[1]	
M550	16 MOD.	550x328x140mm	28W		1/3				3
	24 MOD.	550x477x150mm							3

[1] .1102: tinted window (standard) + with label + with triangular key + with IP00 connection devices 2(5x10mm² - 5x16mm²)

- Power dissipation calculated in conformity with CEI 23-49 italian standards

- 16A (70x87mm) or, with suitable adaption, 32A socket (84x106mm).

