

■ SURFACE MOUNTING VERSION >> MODULAR CONSUMER UNITS >> WITH WINDOW



IP: IP40
Modularity: 8 DIN

No. modules	Dimensions (hxbxd)	Power	Colour	Code	
8+1 MOD.	190x254x108mm	17W		673.2008B	1/12
		17W		673.2008B.1101 ²⁾	1/12
		17W		673.2008B.2010 ³⁾	1/12
		17W		673.2008B.2012 ⁴⁾	1/10
		17W		673.2008	1/12
		17W		673.2008.1102 ¹⁾	1/12

Power dissipation calculated in conformity with CEI 23-49 italian standards.

(* Power dissipation calculated when 2 consumer units are on top of each other joined by specially designed accessories.

¹⁾.1102: tinted window (standard), with label, with triangular key, with 2 IP00 terminal blocks (5x10mm² - 5x16mm²).

²⁾.1101: tinted window (standard), with label, with triangular key, with 1 IP00 terminal block (5x10mm² - 5x16mm²).

³⁾.2010: white window, without label, without locking kit, without terminal block.

⁴⁾.2012: white window, without label, without locking kit, with 2 IP00 terminal blocks (5x10mm² - 5x16mm²).



IP: IP40
Modularity: 12 DIN

No. modules	Dimensions (hxbxd)	Power	Colour	Code	
12+1 MOD.	250x326x108mm	24W (48W*)		673.2012B	1/7
		24W (48W*)		673.2012B.1101 ²⁾	1/7
		24W (48W*)		673.2012B.2010 ³⁾	1/7
		24W (48W*)		673.2012B.2012 ⁴⁾	1/6
		24W (48W*)		673.2012	1/7
		24W (48W*)		673.2012.1102 ¹⁾	1/6

Power dissipation calculated in conformity with CEI 23-49 italian standards.

(* Power dissipation calculated when 2 consumer units are on top of each other joined by specially designed accessories.

¹⁾.1102: tinted window (standard), with label, with triangular key, with 2 IP00 terminal blocks (5x10mm² - 5x16mm²).

²⁾.1101: tinted window (standard), with label, with triangular key, with 1 IP00 terminal block (5x10mm² - 5x16mm²).

³⁾.2010: white window, without label, without locking kit, without terminal block.

⁴⁾.2012: white window, without label, without locking kit, with 2 IP00 terminal blocks (5x10mm² - 5x16mm²).



IP: IP40
Modularity: 18 DIN

No. modules	Dimensions (hxbxd)	Power	Colour	Code	
18+1 MOD.	250x434x140mm	42W (74W*)		673.2018B	1/6
		42W (74W*)		673.2018B.1101 ²⁾	1/6
		42W (74W*)		673.2018B.2010 ³⁾	1/6
		42W (74W*)		673.2018B.2012 ⁴⁾	1
		42W (74W*)		673.2018	1/6

Power dissipation calculated in conformity with CEI 23-49 italian standards.

(* Power dissipation calculated when 2 consumer units are on top of each other joined by specially designed accessories.

¹⁾.1102: tinted window (standard), with label, with triangular key, with 2 IP00 terminal blocks (5x10mm² - 5x16mm²).

²⁾.1101: tinted window (standard), with label, with triangular key, with 1 IP00 terminal block (5x10mm² - 5x16mm²).

³⁾.2010: white window, without label, without locking kit, without terminal block.

⁴⁾.2012: white window, without label, without locking kit, with 2 IP00 terminal blocks (5x10mm² - 5x16mm²).