


**IP: IP40**  
**Modularity: 24 DIN**

No. modules	Dimensions (hxbxd)	Power	Colour	Code	
24+4 MOD.	400x326x108mm	35W (63W*)		673.4024B	1/5
		35W (63W*)		673.4024B.1102 <sup>1)</sup>	1/5
		35W (63W*)		673.4024B.2010 <sup>3)</sup>	1/5
		35W (63W*)		673.4024B.2012 <sup>4)</sup>	1
		35W (63W*)		673.4024	1/5

Power dissipation calculated in conformity with CEI 23-49 italian standards.

(\* Power dissipation calculated when 2 consumer units are on top of each other joined by specially designed accessories.

<sup>1)</sup>.1102: tinted window (standard), with label, with triangular key, with 2 IP00 terminal blocks (5x10mm<sup>2</sup> - 5x16mm<sup>2</sup>).

<sup>2)</sup>.1101: tinted window (standard), with label, with triangular key, with 1 IP00 terminal block (5x10mm<sup>2</sup> - 5x16mm<sup>2</sup>).

<sup>3)</sup>.2010: white window, without label, without locking kit, without terminal block.

<sup>4)</sup>.2012: white window, without label, without locking kit, with 2 IP00 terminal blocks (5x10mm<sup>2</sup> - 5x16mm<sup>2</sup>).


**IP: IP40**  
**Modularity: 36 DIN**

No. modules	Dimensions (hxbxd)	Power	Colour	Code	
36+4 MOD.	400x434x140mm	57W (96W*)		673.4036B	1/4
		57W (96W*)		673.4036B.1102 <sup>1)</sup>	1/4
		57W (96W*)		673.4036B.2010 <sup>3)</sup>	1/4
		57W (96W*)		673.4036B.2012 <sup>4)</sup>	1
		57W (96W*)		673.4036	1/4

Power dissipation calculated in conformity with CEI 23-49 italian standards.

(\* Power dissipation calculated when 2 consumer units are on top of each other joined by specially designed accessories.

<sup>1)</sup>.1102: tinted window (standard), with label, with triangular key, with 2 IP00 terminal blocks (5x10mm<sup>2</sup> - 5x16mm<sup>2</sup>).

<sup>2)</sup>.1101: tinted window (standard), with label, with triangular key, with 1 IP00 terminal block (5x10mm<sup>2</sup> - 5x16mm<sup>2</sup>).

<sup>3)</sup>.2010: white window, without label, without locking kit, without terminal block.

<sup>4)</sup>.2012: white window, without label, without locking kit, with 2 IP00 terminal blocks (5x10mm<sup>2</sup> - 5x16mm<sup>2</sup>).


**IP: IP40**  
**Modularity: 54 DIN**

No. modules	Dimensions (hxbxd)	Power	Colour	Code	
54+5 MOD.	550x434x140mm	75W (125W*)		673.5054B	1/2
		75W (125W*)		673.5054B.1101 <sup>2)</sup>	1/2
		75W (125W*)		673.5054B.2010 <sup>3)</sup>	1/2
		75W (125W*)		673.5054B.2012 <sup>4)</sup>	1
		75W (125W*)		673.5054	1/2

Power dissipation calculated in conformity with CEI 23-49 italian standards.

(\* Power dissipation calculated when 2 consumer units are on top of each other joined by specially designed accessories.

<sup>1)</sup>.1102: tinted window (standard), with label, with triangular key, with 2 IP00 terminal blocks (5x10mm<sup>2</sup> - 5x16mm<sup>2</sup>).

<sup>2)</sup>.1101: tinted window (standard), with label, with triangular key, with 1 IP00 terminal block (5x10mm<sup>2</sup> - 5x16mm<sup>2</sup>).

<sup>3)</sup>.2010: white window, without label, without locking kit, without terminal block.

<sup>4)</sup>.2012: white window, without label, without locking kit, with 2 IP00 terminal blocks (5x10mm<sup>2</sup> - 5x16mm<sup>2</sup>).

## Product code reading

Consumer units	Additional features
673.2008B	A B C D

**A**  
 Window  
  
 1: tinted window (standard)  
 2: white window

**B**  
 Self-adhesive label for identification data  
  
 0: without label  
 1: with label

**C**  
 Locking kit  
  
 0: with triangular key  
 2: Yale key locking kit

**D**  
 Terminal block  
  
 IP00  
 0: without connection device  
 1: 1 (5x10 mm<sup>2</sup> - 5x16 mm<sup>2</sup>)  
 2: 2 (5x10 mm<sup>2</sup> - 5x16 mm<sup>2</sup>)  
 3: n° = DIN