

**IP44**



**OLBIA | 8016909**



**OLBIA | 8001402**




**DRIVER | 9020171**


Driver 12W Eaglerise  
Input: 100-240V AC 50/60Hz  
Output: 12-24VDC 500mA  
Not Dimmable



**OLBIA | 8059409**



**OLBIA | 8033409**



**8016905** | 10W · 3000K  
**8016906** | 10W · 4000K

Photo	Code	Material	Recessed	CRI	UGR	LED Chip	Dimension (cm)	Cut Out (cm)	Beam Angle	Kelvin	Protection	Adjustable	Driver Included
	8016909	White & Black Alum.	✓	>90	<28	X	L:9 H:8.9	8x8	36°	X	IP44	X	X
	8001402	White Aluminium	✓	>90	<28	X	L:9 H:8.9	8x8	36°	X	IP44	X	X
	8059409	White & Black Alum.	✓	>90	<16	X	L:16 W:9 H:8.9	15x7.7	36°	X	IP44	X	X
	8033409	White Aluminium	✓	>90	<16	X	L:16 W:9 H:8.9	15x7.7	36°	X	IP44	X	X

**MUST HAVE ACCESSORY**

Photo	Code	Material	Watt	Volt	Ma	LED Chip	Dimension (cm)	Lumen	CRI	Beam Angle	Kelvin	Protection	Dimmable	Driver Included
	8016905	Black Aluminium	10W	20V	500	Citizen	D:6.3 H:3.8	810Lm	>90	X	3000K	IP44	X	X
	8016906	Black Aluminium	10W	20V	500	Citizen	D:6.3 H:3.8	810Lm	>90	X	4000K	IP44	X	X

**DON'T FORGET TO CONNECT THEM WITH DRIVER | code: 9020171**

