

### Terminal strips

CONNECTO Series

815.



Description	Connecting capacity	Volt	Dimension	Pitch	Ø fixing hole	Colour	T85 terminal strips
TERMINAL BLOCK T85	2,5mm <sup>2</sup>	250V	95,5x15,5x16mm	8mm	2,6mm		<b>815.2361B</b> 50/800
							<b>815.2361</b> 50/800
	4mm <sup>2</sup>	450V	120x16,6x17,4mm	10mm	3,5mm		<b>815.2362B</b> 50/400
							<b>815.2362</b> 50/400
	6mm <sup>2</sup>	450V	120x16,6x17,4mm	10mm	3,5mm		<b>815.23625B</b> 50/400
							<b>815.23625</b> 50/400
	10mm <sup>2</sup>	750V	138x23,5x20,5mm	11,5mm	4,3mm		<b>815.2363B</b> 25/300
							<b>815.2363</b> 25/300
	16mm <sup>2</sup>	750V	174x30x24mm	14,5mm	4,3mm		<b>815.2364B</b> 25/150
							<b>815.2364</b> 25/150
	25mm <sup>2</sup>	750V	210x38x36mm	17,5mm	4,3mm		<b>815.2365B</b> 15/60
							<b>815.2365</b> 15/60
35mm <sup>2</sup>	750V	264x46x39mm	22mm	5,5mm		<b>815.2366B</b> 10/40	
						<b>815.2366</b> 10/40	

- Self-extinguishing material in compliance with IEC 60695-2-1 standard 850°C.
- Engineering plastic casing
- Max. service temperature - continuous duty: 85°C.
- Nickel-plated brass terminal
- 12 poles
- Captive screws of zinc-plated steel

3.2

