

corpuri de iluminat cu LED - IP65 & stalpi IP54



25000 ore
de funcționare




rotund 8W



h:0,7m

- Corp de iluminat cu montaj aparent
- Lumina indirecta
- Material : Policarbonat
- Putere maxima : 8W
- Sistem de pornire inclus



alb grafit gri



IP65



COD	TENSIUNE (V)	CULOARE	PUTERE (W)	LUMINA	LUMEN (lm)	DIMENSIUNI		PACK. (buc)
						D (mm)	h (mm)	
9-8980	230V	alb	8W	calda 3000k	640	165	58	1/24
9-8981	230V	grafit	8W	calda 3000k	640	165	58	1/24
9-8986	230V	gri	8W	calda 3000k	640	165	58	1/24

COD	DENUMIRE	PUTERE (W)	LUMINA	LUMEN (lm)	DIMENSIUNI		PACK. (buc)
					D (mm)	h (mm)	
9-89981	stalp 0,7m & corp - grafit	8W	calda 3000k	640	165	700	1/6
9-89986	stalp 0,7m & corp - gri	8W	calda 3000k	640	165	700	1/6



25000 ore
de funcționare




patrat 8W



h:0,7m

- Corp de iluminat cu montaj aparent
- Lumina indirecta
- Material : Policarbonat
- Putere maxima : 8W
- Sistem de pornire inclus



alb grafit gri



IP65



COD	TENSIUNE (V)	CULOARE	PUTERE (W)	LUMINA	LUMEN (lm)	DIMENSIUNI		PACK. (buc)
						D (mm)	h (mm)	
9-89080	230V	alb	8W	calda 3000k	640	150x150	58	1/18
9-89081	230V	grafit	8W	calda 3000k	640	150x150	58	1/18
9-89086	230V	gri	8W	calda 3000k	640	150x150	58	1/18

COD	DENUMIRE	PUTERE (W)	LUMINA	LUMEN (lm)	DIMENSIUNI		PACK. (buc)
					D (mm)	h (mm)	
9-89981	stalp 0,7m & corp - grafit	8W	calda 3000k	640	150x150	700	1/10
9-89986	stalp 0,7m & corp - gri	8W	calda 3000k	640	150x150	700	1/10