

Alvis 2000

PN: AVRL-20002AL-CS01B
EAN: 6422956012793

Specifications

Capacity	2000 VA / 1200 W
Socket type	2 x Schuko
Input	
Nominal voltage	230 VAC
Accepted voltage range	150 VAC - 270 VAC
Frequency range	50 Hz or 60 Hz
Output	
Nominal voltage	230 VAC
Voltage regulation	± 8%
Efficiency	
Normal mode	> 95%
Protection	
Delay time	180 Seconds
Full protection	Over-voltage, Under-voltage, Overheat, Overload protection, Surge protection
Surge rating energy	220 Joules
Indicators	
LED indicator	Normal indicator, AVR indicator, Delay time setting, Fault indicator
Normal mode	Green lighting
Delay	Yellow & Green LED lighting
Protecting (Output cut off)	Red & Green LED lighting
Digital display	Input and output voltage
Environment	
Humidity	10 - 90 % (non-condensing)
Temperature	-10 - 40°C



Digital display



Time delay function



Toroidal Transformer




- Microprocessor control guarantees high reliability
- Time delay function eliminates transients that can effect connected equipment
- Under-voltage, over-voltage, over-heat and over current protection
- Provides stable output voltage
- Provide surge and spike suppression

Physical

Product dimensions	250 x 140 x 175 mm
Product weight	4.2 kg
Retail pack dimensions	305 x 165 x 213 mm



Logistics

 Carton Box Size (LxWxH)	350 x 320 x 450 mm
 Pieces in the Carton Box	4
 Net & Gross weight / CTN	NW: 17.64 / GW: 18.24 kg

Certificates

RoHS 
2011/65/EU