F&F Filipowski sp.k., ul. Konstantynowska 79/81, 95-200 Pabianice, tel.: +48 (42) 214 90 37, e-mial: biuro@fif.com.pl, www.fif.com.pl



CP-721-FPV

Programmable voltage relay

Index: CP-721-FPV

5 902431 675077

TECHNICAL DATA

Depth	65 mm
Height	90 mm
Width	35 mm
Rated switch current	8 A
Number of contacts as change-over contact	2
Number of contacts as normally open contact	0
Number of contacts as normally closed contact	0
Max. permitted off-delay time	10 s
Min. adjustable off-delay time	2 s
Max. permitted delay-on energization time	1 s
Min. adjustable delay-on energization time	0.1 s
With detachable clamps	Nie
External power supply required	Nie
Response value voltage	150-260 V
Single-phase under voltage possible	Tak
Three-phase under voltage possible	Nie
Single-phase overvoltage possible	Tak
Three-phase overvoltage possible	Nie
Single-phase hysteresis possible	Tak
Three-phase hysteresis possible	Nie
Contains function DC-under voltage	Nie
Contains function DC overvoltage	Nie
Contains function DC-voltage hysteresis	Nie
Type of electric connection	Screw connection
Voltage type (supply voltage)	AC
Type of voltage measuring range	AC
Voltage type (operating voltage)	AC

Manual

CE declaration

Certificate

2025 Copyrights: www.fif.com.pl

e-mail: biuro@fif.com.pl