

Industrial power supply for a DIN rail, 24VDC, 2.5A, 60W, plastic housing

Marka: Orno | Symbol: OR-PSU-1663 | Ean: 5908254824944

ORNO


PRODUCT DESCRIPTION

Industrial power supply for a DIN rail, 24VDC, 2.5A, 60W, plastic housing.

TECHNICAL DATA

General information:

Voltage type of supply voltage:	AC
1st secondary output voltage at DC [V]:	24
Max. output current 1 [A]:	2.5
Max. Overload [%]:	150
Max. Overcurrent [V]:	180
Secondary voltage adjustable [V]:	5-48
Short-circuit-proof:	Tak
Rated supply voltage at AC 50 Hz [V]:	85-264
Rated supply voltage at AC 60 Hz [V]:	85-264
Output voltage stabilized:	Tak
Line Regulation:	±1%
Power output [W]:	60
Efficiency:	88
Stabilized:	Tak
Type of electric connection:	Połączenie Śrubowe
Rail mounting possible:	Tak
Wall mounting possible:	Nie
Direct mounting possible:	Nie
Width [mm]:	41
Height [mm]:	92
Depth [mm]:	100
Degree of protection (IP):	IP20
Operating Temperature:	[-20 do +60]
Storage Temp:	[-40 do +85]
Storage Humidity(RH):::	[10 do 95%]

Working Humidity(RH): / wilgotność podczas pracy (bez kondensacji):

[20 do 90%]

Compliance with standards:

EN55032 (CISPR32), EN61204-3, EN61000-3-2,-3, EAC TP TC 020,CNS1348, UL508, EN62368-1, EAC TP TC 004, CNS14336-1 AS/NZS 62368.1



