

## TECHNICAL CARD



Tactical LED Flashlight

# VIDEX®



## WARRANTY 3 YEARS

### COLD WHITE



### 6500K

Cold White / Zimna biel / Studena bila / Blanc froid / Studená biela / Koud wit / Hideg feher / Hladno bela / Hladno bijela / Kaltweiß / Alb rece / Šalta balta / Auksti balta / Kūlm valge.

## General parameters

Operation mode	TURBO, MIDDLE, MOON, STROBE
Light source replaceable	no
Battery Warranty	1 year

## Type of light source

Dimmable	no
Technology	LED

## Electrical parameters

On-mode power (Pon)	20 W
Input interface	USB-C

## Photometric parameters

Useful luminous flux of the contained light source (Φ <sub>use</sub> )	2000 Lm
Peak luminous intensity	95600 cd

## VIDEX VLF-AT265 2000Lm 6500K

### INDEX: VLF-AT265

Correlated color temperature 6500K (cold white)

## Additional information

Housing colour	Black
Fall protection	3 m
Operating temperature range	-20° +40°C
Battery voltage	3.7 V
Battery type	Li-ion 21700, Li-ion 18650
Battery capacity	4000 mAh
Battery indicator	5 level
Battery replaceable	yes
Mercury content	Does not contain
Ingress protection	IP68
Housing material	Heavy-anodized aircraft aluminum

## Dimensions

EAN	4820246484237
Height	145 mm
Depth	31 mm
In the package	1 pc.
Outer box	20 pcs.
Width	40 mm
Unit nett weight	163g

## Signs marking goods

Packaging marking CE, Utilization

**VIDEX<sup>®</sup>**

VIDEX VLF-AT265 2000Lm 6500K

**INDEX: VLF-AT265**

**VIDEX®**

VIDEX VLF-AT265 2000Lm 6500K

**INDEX: VLF-AT265**

# VIDEX®

VIDEX VLF-AT265 2000Lm 6500K

INDEX: VLF-AT265



We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,  
30-732 Krakow, Poland.



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



— The protection is effective in case of a fall from a height of up to 3 meters



Not Dimmable

— The product is incompatible with light regulators



-20° +40°C

— Operating temperatures range



Free

— The product does not contain mercury



IP68

— Class of protection against dust and moisture. The product has full protection against dust and prolonged immersion in water at a depth of more than 1 meter

Date: 10.10.2025