

## TECHNICAL CARD



LED Headlamp

# VIDEX®



## WARRANTY 3 YEARS

### COLD WHITE



### 6500K

Cold White / Zimna biel / Studena bila / Blanc froid / Studená biela / Koud wit / Hideg feher / Hladno bela / Hladno bijela / Kaltweiß / Alb rece / Šalta balta / Auksti balta / Kūlm valge.

## General parameters

Operation mode	HIGH, LOW, STROBE, RED ON, RED FLASH
Light source replaceable	no
Battery Warranty	1 year

## Type of light source

Dimmable	no
Technology	LED

## Electrical parameters

On-mode power (Pon)	20 W
Input interface	USB-C

## Photometric parameters

Useful luminous flux of the contained light source (Φ <sub>use</sub> )	1400 Lm
Peak luminous intensity	6480 cd

## VIDEX VLF-H056 1400Lm 6500K

### INDEX: VLF-H056

Correlated color temperature 6500K (cold white)

## Additional information

Housing colour	Black
Fall protection	1 m
Operating temperature range	-20° +40°C
Battery voltage	3.7 V
Battery type	Li-ion 18650 (2pcs)
Battery capacity	2200 mAh (2pcs)
Battery indicator	5 level
Battery replaceable	yes
Mercury content	Does not contain
Ingress protection	IP65
Housing material	PC

## Dimensions

EAN	4820246481632
Height	48 mm
Depth	32 mm
In the package	1 pc.
Outer box	20 pcs.
Width	65 mm
Unit nett weight	171g

## Signs marking goods

Packaging marking	CE, Utilization
-------------------	-----------------

**VIDEX®**

VIDEX VLF-H056 1400Lm 6500K

**INDEX: VLF-H056**

# VIDEX®

## VIDEX VLF-H056 1400Lm 6500K

### INDEX: VLF-H056



We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,  
30-732 Krakow, Poland.



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



— The protection is effective in case of a fall from a height of up to 1 meter



— The product is incompatible with light regulators



— Operating temperatures range



— The product does not contain mercury



— Class of protection against dust and moisture. The product has full protection against dust and water jets from all directions

Date: 10.10.2025