



CARACTERISTICI



- culori: argintiu ☐ negru ☐
- carcasa plastic
- montare pe suprafete orizontale & verticale
- indicator optic de stare (3 LEDuri)
- intrerupator cu decuplare automata / manuala
- aplicatii: electronice, centrala termica / electrocasnice mici

PROTECTIE



- functie 2 in 1: stabilizator si protectie prin intermediul microprocesorului intern
- protectie contra varfurilor de tensiune extreme de scurta durata
- protectie la suprasarcina, supraincalzire si scurt-circuit
- clasa de izolare electrica: IP20

TED 2100VA-SVC cu servomotor

SPECIFICATII TEHNICE



OPTIUNEA 2100VA

Putere	1200W
Tensiune / Frecventa intrare	130-260V AC / 50-60Hz
Tensiune / Frecventa iesire	230V / 50Hz
Precizie la iesire	+/- 1-3%
Conectori iesire	2x Schuko
Unda / Eficienta	sinusoidala pura / 98%
Dimensiuni (L x l x i)	255 x 168 x 146 mm
Greutate	6.2 kg
Nivel zgomot	< 20dB (1m distanta)
Temperatura functionare	0°C pana la 40°C
Umiditate functionare	20%-90% fara condens
Cod produs	A0057958



APLICATII

CARACTERISTICI



- culori: argintiu ☐
- carcasa metalica
- 1x maner pentru manipulare usoara / transport
- display digital: tensiune in/out; supratensiune / subtensiune, posibile erori (overheat, unusual, delay)
- aplicatii: centrala termica, electronice, electrocasnice mici/medii



PROTECTIE



- functie 2 in 1: stabilizator si protectie prin intermediul microprocesorului intern
- protectie la suprasarcina, supraincalzire, supratensiune si scurt-circuit
- alarma sonora
- clasa de izolare electrica: IP20

