




EMOS sockets, wall switches IP54,44




- installation: onto a wall
- enclosure: IP54, IP44
- double socket is internally interconnected

A1398 1/5/-/60
31 04 139 800 EF600SA




product: alternating switch - no. 6 = type: 250 V~/10 AX = colour: grey-black = type of mounting: on the wall = IP rating: IP54 = version: 1 button stairway, waterproof = packaging: 1 pc, PE packet

A1398.1 1/5/-/60
31 04 139 811 EF602S
(EF602SA)




product: serial switch no. 5 (chandelier) = type: 250 V~/10 AX = colour: grey-black = type of mounting: on the wall = IP rating: IP54 = version: 2 buttons classic water-resistant = packaging: 1 pc, PE packet

A1398.2 1/5/-/60
19 50 011 202 EF600SB





product: cross switch no. 7 = type: 250 V~/10 AX = colour: grey-black = type of mounting: on the wall = IP rating: IP54 = version: 1 button = packaging: 1 pc, PE packet

A1399 1/5/-/60
19 50 011 201 EF600SD




product: switch controller (1/0) = type: 250 V~/10 A = colour: grey-black = type of mounting: on the wall = IP rating: IP54 = version: 1 button = packaging: 1 pc, PE packet

A1396 1/5/-/60
31 04 139 600 EF600G




product: socket with earthing pin and lid = design: SCHUKO = type: 250 V~/16 A max. = colour: grey-black = type of mounting: on the wall = IP rating: IP44 = version: single water-resistant = packaging: 1 pc, PE packet

A1398.3 1/5/-/60
19 50 011 203 EF600SA-B




product: alternating switch no. 6 = type: 250 V~/10 AX = colour: white = type of mounting: on the wall = IP rating: IP54 = version: 1 button stairway, waterproof = packaging: 1 pc, PE packet

A1396.1 1/5/-/25
31 04 139 611 EF602G

product: double socket with earthing pins and lids with interconnection = design: SCHUKO = type: 250 V~/16 A max. = colour: grey-black = type of mounting: on the wall = IP rating: IP44 = version: double water-resistant = packaging: 1 pc, PE packet

A1398.4 1/5/-/60
19 50 011 204 EF602S-B

product: serial switch no. 5 (chandelier) = type: 250 V~/10 AX = colour: white = type of mounting: on the wall = IP rating: IP54 = version: 2 buttons classic water-resistant = packaging: 1 pc, PE packet