

Product Benefits

- Easy & quick installation
- Energy efficient and long lasting
- Excellent color rendering index(CRI)
- Saves up to %80 Energy
- No UV and IR radiation
- Tool free installation
- Suitable for Ceiling use

Applications

- General indoor lighting
- Shops, offices
- Hotels, hospitals
- Homes, living areas
- Schools, showrooms
- Cafe, restaurants





MODEL NO	TYPE	BODY COLOR	CCT	WATT	LUMEN	VOLTAGE	CRI	P.F.	ANGLE	CUTOUT	MATERIAL	PCS/CTN
BP01-30300	SMD-CRD	White	3000K	3W	150Lm	220V-240VAC	>80	>0.55	120°	Ø71	Aluminium	40
BP01-30310	SMD-CRD	White	4000K	3W	150Lm	220V-240VAC	>80	>0.55	120°	Ø71	Aluminium	40
BP01-30330	SMD-CRD	White	6500K	3W	150Lm	220V-240VAC	>80	>0.55	120°	Ø71	Aluminium	40
BP01-30600	SMD-CRD	White	3000K	6W	350Lm	220V-240VAC	>80	>0.55	120°	Ø105	Aluminium	40
BP01-30610	SMD-CRD	White	4000K	6W	350Lm	220V-240VAC	>80	>0.55	120°	Ø105	Aluminium	40
BP01-30630	SMD-CRD	White	6500K	6W	350Lm	220V-240VAC	>80	>0.55	120°	Ø105	Aluminium	40
BP01-31200	SMD-CRD	White	3000K	12W	910Lm	220V-240VAC	>80	>0.55	120°	Ø155	Aluminium	20
BP01-31210	SMD-CRD	White	4000K	12W	910Lm	220V-240VAC	>80	>0.55	120°	Ø155	Aluminium	20
BP01-31230	SMD-CRD	White	6500K	12W	910Lm	220V-240VAC	>80	>0.55	120°	Ø155	Aluminium	20

This luminaire contains built-in LED lamps.

The lamps cannot be changed in the luminaire.

BRAYTRON 874/2012



*Technical information indicated above may have tolerance ±%10. For final updated information please visit website www.braytron.com