



**Product Benefits**

- Easy & quick installation
- Energy efficient and long lasting
- Excellent color rendering index(CRI)
- Saves up to %80 Energy
- No UV and IR radiation
- Tool free installation
- Suitable for Ceiling use

**Applications**

- General indoor lighting
- Shops, offices
- Hotels, hospitals
- Homes, living areas
- Schools, showrooms
- Cafe, restaurants



MODEL NO	TYPE	BODY COLOR	CCT	WATT	LUMEN	VOLTAGE	CRI	P.F.	ANGLE	MATERIAL	PCS/CTN
BP04-31200	SMD-SRD	White	3000K	12W	910Lm	220V-240VAC	>80	>0.55	120°	Aluminium	20
BP04-31210	SMD-SRD	White	4000K	12W	910Lm	220V-240VAC	>80	>0.55	120°	Aluminium	20
BP04-31230	SMD-SRD	White	6500K	12W	910Lm	220V-240VAC	>80	>0.55	120°	Aluminium	20
BP04-31800	SMD-SRD	White	3000K	18W	1360Lm	220V-240VAC	>80	>0.55	120°	Aluminium	20
BP04-31810	SMD-SRD	White	4000K	18W	1360Lm	220V-240VAC	>80	>0.55	120°	Aluminium	20
BP04-31830	SMD-SRD	White	6500K	18W	1360Lm	220V-240VAC	>80	>0.55	120°	Aluminium	20
BP04-32400	SMD-SRD	White	3000K	24W	1850Lm	220V-240VAC	>80	>0.55	120°	Aluminium	10
BP04-32410	SMD-SRD	White	4000K	24W	1850Lm	220V-240VAC	>80	>0.55	120°	Aluminium	10
BP04-32430	SMD-SRD	White	6500K	24W	1850Lm	220V-240VAC	>80	>0.55	120°	Aluminium	10
BP04-33600	SMD-SRD	White	3000K	36W	2500Lm	220V-240VAC	>80	>0.95	120°	Aluminium	10
BP04-33610	SMD-SRD	White	4000K	36W	2500Lm	220V-240VAC	>80	>0.95	120°	Aluminium	10
BP04-33630	SMD-SRD	White	6500K	36W	2500Lm	220V-240VAC	>80	>0.95	120°	Aluminium	10

This luminaire contains built-in LED lamps.

The lamps cannot be changed in the luminaire.

**LED**

BRAYTRON 874/2012


12W 170x170 31

18W 210x210 31

24W 300x300 31

36W 400x400 38

CE EAC LVD EMC ErP COMPLIANT RoHS Hg 0.0mg IP 20 Non-Halogen >25,000 -20°C +40°C



\*Technical information indicated above may have tolerance ±%10.For final updated information please visit website [www.braytron.com](http://www.braytron.com)