



**Features**

- Easy & quick installation
- Energy efficient and long lasting
- Saves up to %80 energy
- Homogenous illuminance
- Aesthetic Design
- Ingress Protection against water
- Suitable for indoor & outdoor ceiling use

**Application**

- General outdoor lighting
- Industrial halls
- Parking lots, Warehouses
- Cold storage rooms





MODEL NO	TYPE	BODY COLOR	CCT	WATT	LUMEN	VOLTAGE	CRI	P.F.	ANGLE	MATERIAL	PCS/CTN
BT07-00610	Proline-IPG	White	4000K	16W	1700Lm	220V-240VAC	>80	>0.55	120°	Plastic	20
BT07-00630	Proline-IPG	White	6500K	16W	1700Lm	220V-240VAC	>80	>0.55	120°	Plastic	20
BT07-01210	Proline-IPG	White	4000K	32W	3400Lm	220V-240VAC	>80	>0.95	120°	Plastic	20
BT07-01230	Proline-IPG	White	6500K	32W	3400Lm	220V-240VAC	>80	>0.95	120°	Plastic	20

This luminaire contains built-in LED lamps.

The lamps cannot be changed in the luminaire.

BRAYTRON 874/2012



\*Technical information indicated above may have tolerance ±%10. For final updated information please visit website [www.braytron.com](http://www.braytron.com)