



Features

- Made from pure die-casting aluminium
- Diffused by PC lens, Suitable For streets
- Built-in high quality AC-Direct driver
- Surge Protection, L to L2kv, L to G 1kv
- IK08 Mechanical external impact
- Polyester powder coating for outdoor use
- Adjustable for different size of pole
- Smart design for better heat dissipation
- Low energy consumption

Application

- Streets & highways
- Garden backyard
- Factory backyards
- Open area parking lots
- Public parks & gardens



LED 20,000 HOURS 2 YEARS WARRANTY IP65 100Lm/w


MODEL NO	TYPE	BODY COLOR	CCT	WATT	LUMEN	VOLTAGE	CRI	P.F.	ANGLE	MATERIAL	PCS/CTN
BT42-03032	ST81	Grey	6500K	30W	3000Lm	220V-240VAC	>70	>0.95	110°	Aluminium	1
BT42-05032	ST81	Grey	6500K	50W	5000Lm	220V-240VAC	>70	>0.95	110°	Aluminium	1
BT42-09132	ST81	Grey	6500K	100W	10000Lm	220V-240VAC	>70	>0.95	110°	Aluminium	1

This luminaire contains built-in LED lamps.

The lamps cannot be changed in the luminaire.

BRAYTRON 874/2012

CE ENEC LVD EMC ErP COMPLIANT RoHS COMPLIANT Hg 0.0mg IP 65 Max. 25,000 hours -20°C to +40°C



*Technical information indicated above may have tolerance ±%10. For final updated information please visit website www.braytron.com