



Features

- Made from pure die-casting aluminium
- Diffused by PC lens, Suitable For streets
- Built-in high quality AC-Direct driver
- Surge Protection, L to L 10kv, L to G 6kv
- IK08 Mechanical external impact
- Polyester powder coating for outdoor use
- Adjustable for different size of pole • Smart design for better heat dissipation
- Low energy consumption

Application

- Streets & highways
- Garden backyard
- Factory backyards
- Open area parking lots
- Public parks & gardens



















MODEL NO	TYPE	BODY COLOR	CCT	WATT	LUMEN	VOLTAGE	CRI	P.F.	ANGLE	MATERIAL	PCS/CTN
BT42-53032	ST95	Grey	6500K	30W	3900Lm	220V-240VAC	>70	>0.95	70x140°	Aluminium	1
BT42-55032	ST95	Grey	6500K	50W	6500Lm	220V-240VAC	>70	>0.95	70x140°	Aluminium	1
BT42-59132	ST95	Grey	6500K	100W	13000Lm	220V-240VAC	>70	>0.95	70x140°	Aluminium	1
BT42-59432	ST95	Grey	6500K	150W	19500Lm	220V-240VAC	>70	>0.95	70x140°	Aluminium	1

















^{*}Technical information indicated above may have tolerance ±%10.For final updated information please visit website www.braytron.com