



MODEL NO	TYPE	DIMMING TYPE	INPUT VOLTAGE	OUTPUT VOLTAGE	INPUT POWER	OUTPUT POWER
BY05-60120	Dimmable Driver	Triac	220V-240VAC	20-40VDC	Max. 13.8W	12W

OUTPUT CURRENT	POWER FACTOR	EFFICIENCY	LIFE TIME	WORKING HUM.	IP	MATERIAL	PCS/CTN
300mA±5%	>0.9	>%86	20000 Hours	<%93RH	IP20	Plastic	200

3 YEARS WARRANTY



A+



MODEL NO	TYPE	DIMMING TYPE	INPUT VOLTAGE	OUTPUT VOLTAGE	INPUT POWER	OUTPUT POWER
BY05-60180	Dimmable Driver	Triac	220V-240VAC	40-60VDC	Max. 20.6W	18W

OUTPUT CURRENT	POWER FACTOR	EFFICIENCY	LIFE TIME	WORKING HUM.	IP	MATERIAL	PCS/CTN
300mA±5%	>0.9	>%86	20000 Hours	<%93RH	IP20	Plastic	125

3 YEARS WARRANTY



A+



MODEL NO	WATT	OUTPUT VOLTAGE	OUTPUT CURRENT	P.F.	VOLTAGE	IP	MATERIAL	DIMENSIONS	PCS/CTN
BY02-00250	25W	12VDC	2A	>0.6	220V-240VAC	IP20	Aluminium	86x58x33	60
BY02-00600	60W	12VDC	5A	>0.6	220V-240VAC	IP20	Aluminium	160x40x32	60
BY02-01000	100W	12VDC	8.5A	>0.6	220V-240VAC	IP20	Aluminium	190x47x35	60
BY02-01500	150W	12VDC	12.5A	>0.6	220V-240VAC	IP20	Aluminium	200x57x40	60
BY02-02000	200W	12VDC	16.5A	>0.6	220V-240VAC	IP20	Aluminium	225x68x40	40
BY02-02500	250W	12VDC	20A	>0.6	220V-240VAC	IP20	Aluminium	220x68x40	40

2 YEARS WARRANTY



MODEL NO	WATT	OUTPUT VOLTAGE	OUTPUT CURRENT	P.F.	VOLTAGE	IP	MATERIAL	DIMENSIONS	PCS/CTN
BY02-10250	25W	24VDC	1A	>0.6	220V-240VAC	IP20	Aluminium	86x58x33	60
BY02-10600	60W	24VDC	2.5A	>0.6	220V-240VAC	IP20	Aluminium	160x40x32	60
BY02-11000	100W	24VDC	4.2A	>0.6	220V-240VAC	IP20	Aluminium	190x47x35	60
BY02-11500	150W	24VDC	6.3A	>0.6	220V-240VAC	IP20	Aluminium	200x57x40	60
BY02-12000	200W	24VDC	8.25A	>0.6	220V-240VAC	IP20	Aluminium	225x68x40	40
BY02-12500	250W	24VDC	10A	>0.6	220V-240VAC	IP20	Aluminium	220x68x40	40

2 YEARS WARRANTY



*Technical information indicated above may have tolerance ±%10. For final updated information please visit website www.braytron.com