



MODEL NO	TYPE	SENSOR TYPE	IP	INPUT VOLTAGE	RATED LOAD	RATED LOAD	RATED LOAD	POWER CONSUMPTION	TIME DELAY	DETECTION ANGLE
BY31-01030	MS03	PIR	IP20	220V-240VAC	800W(Halogen)	150W(CFL)	250W(LED)	0.45W(Static 0.1W)	5 Sec.-8 Min (Adjustable)	180°
DETECTION DISTANCE	DETECTION SPEED	AMBIENT LIGHT	INSTALLATION HEIGHT	WORKING TEMPERATURE	WORKING HUMIDITY	MATERIAL	PCS/CTN			
30 Mt Max.24°	0.6-1.5 m/S	5-2000LUX	1.8-3.5 Mt	-20°-+40°	%93 RH	Plastic	50			





2 YEARS WARRANTY



MODEL NO	TYPE	SENSOR TYPE	IP	INPUT VOLTAGE	RATED LOAD	RATED LOAD	RATED LOAD	POWER CONSUMPTION	TIME DELAY	DETECTION ANGLE
BY31-01010	MS01	PIR	IP20	220V-240VAC	2000W(Halogen)	500W(CFL)	800W(LED)	0.45W(Static 0.1W)	5 Sec.-5 Min (Adjustable)	360°
DETECTION DISTANCE	DETECTION SPEED	AMBIENT LIGHT	INSTALLATION HEIGHT	WORKING TEMPERATURE	WORKING HUMIDITY	MATERIAL	PCS/CTN			
16 Mt Max. 24°	0.6-1.5 m/S	5-2000LUX	1.5-3.5 Mt	-20°-+40°	%93 RH	Plastic	50			





2 YEARS WARRANTY



MODEL NO	TYPE	SENSOR TYPE	IP	INPUT VOLTAGE	RATED LOAD	RATED LOAD	RATED LOAD	POWER CONSUMPTION	TIME DELAY	DETECTION ANGLE
BY31-01040	MS04	PIR	IP20	220V-240VAC	800W(Halogen)	150W(CFL)	250W(LED)	0.45W(Static 0.1W)	5 Sec.-5 Min (Adjustable)	360°
DETECTION DISTANCE	DETECTION SPEED	AMBIENT LIGHT	INSTALLATION HEIGHT	WORKING TEMPERATURE	WORKING HUMIDITY	MATERIAL	PCS/CTN			
6 Mt Max. 24°	0.6-1.5 m/S	5-2000LUX	2-4 Mt	-20°-+40°	%93 RH	Plastic	100			



2 YEARS WARRANTY



*Technical information indicated above may have tolerance ±%10. For final updated information please visit website www.braytron.com