

WATERTIGHT BOARDS

transparent door



Technical Characteristic

Watertight Boards in Thermoplastic Material for Protection Devices for Residential, Commercial and Industrial Areas.

- Ral 7035 Grey
- ABS-PC Material
- Halogen Free
- IK 10 - GWT 650°C
- Triangle Lock-Key
- PUR Material for High Quality Sealing
- Included 1mm. Galvanized Mounting Plate
- Included Wall Fixing Bracket
- Operating Temperature , -25 to +60C



Watertight Boards - Transparent Door

Code	Dimension (WxHxD)	No. Locks	Pack
CP 5011	210x280x130	1	1
CP 5020	250x300x130	1	1
CP 5012	250x330x130	1	1
CP 5012 D	250x350x150	1	1
CP 5013	300x400x165	2	1
CP 5013 D	300x400x195	2	1
CP 5014	400x500x175	2	1
CP 5014 D	400x500x245	2	1
CP 5015	400x600x200	2	1
CP 5016 Y	500x700x245	2	1
CP 5017	350x500x195	2	1
CP 5031	300x350x165	1	1
CP 5032	180x240x120	1	1



Watertight Boards - Transparent Door

Code	Dimension (WxHxD)	No. Locks	Pack
CP 5016	500x700x245	2	1
CP 5018	500x600x220	2	1
CP 5019	600x800x260	3	1

- * Reversible door direction
- * Adjustable mounting plate



Safety Lock with Handle

Code	Description	Pack
CP 5000	Lock for Watertight Boards (2 keys)	1