

# WATERTIGHT BOARDS

with roof



## Technical Characteristic

Watertight Boards in Thermoplastic Material for Protection Devices for Residential, Commercial and Industrial Areas.

- Ral 7035 Grey
- ABS-PC Material
- Halogen Free
- IK 10 - GWT 650°C
- Triangle Lock-Key
- PUR Material for High Quality Sealing
- Included 1mm. Galvanized Mounting Plate
- Included Wall Fixing Bracket
- Operating Temperature , -25 to +60C



### Blank Door - With Roof

Code	Dimension (WxHxD)	No. Locks	Pack
CP 5603	300x400x165	2	1
CP 5604	400x500x175	2	1
CP 5605	400x600x200	2	1
CP 5606	500x700x245	2	1
CP 5607	350x500x195	2	1
CP 5608	500x600x220	2	1
CP 5609	600x800x260	3	1

CP 5609 ÜRETİYOR MUYUZ?



### Transparent Door - With Roof

Code	Dimension (WxHxD)	No. Locks	Pack
CP 5613	300x400x165	2	1
CP 5614	400x500x175	2	1
CP 5615	400x600x200	2	1
CP 5616	500x700x245	2	1
CP 5617	350x500x195	2	1
CP 5618	500x600x220	2	1
CP 5619	600x800x260	3	1



### Safety Lock with Handle

Code	Description	Pack
CP 5000	Lock for Watertight Boards (2 keys)	1



Y. PLS. 00000001  
Y. PLS. 00000002  
Y. PLS. 00000003  
ÇP 5000 01 GİBİ  
ÜRÜN KODLARI  
MEVCUT KENDİNDEN  
ANAHTARLI KİLİT

EKLENECEK Mİ?