

CURVED SAFETY GLASS DOOR CABINETS

▶ floor mounting & surface mounting

Technical Characteristic



- Usage for installation of electrical instruments
- Easy and Fast Installation
- Wide Space for the Cabling
- Pre-Drilled Entries For an Easy Installation
- Tempered Glass Door
- Thickness is 1.20 mm



CPD - Surface Mounting Distribution Cabinets - with mounting plate

Code	Dimension (WxHxD)	DIN Rail Modules	Pack
CPD 4005015 SUM	400x500x150	Mounting Plate	1
CPD 4006515 SUM	400x650x150	Mounting Plate	1
CPD 4505015 SUM	450x500x150	Mounting Plate	1
CPD 4506515 SUM	450x650x150	Mounting Plate	1



CPD Surface Mounting Distribution Cabinets with Din rail Accessory + Blank Cover

Code	Dimension (WxHxD)	DIN Rail Modules	Pack
CPD 4005015 SUPP	400x500x150	30M (15x2 rows)	1
CPD 4006515 SUPP	400x650x150	45M (15x3 rows)	1
CPD 4505015 SUPP	450x500x150	34M (17x2 rows)	1
CPD 4506515 SUPP	450x650x150	51M (17x3 rows)	1



CPD Surface Distribution Cabinets - with Din Rail Accessory

Code	Dimension (WxHxD)	DIN Rail Modules	Pack
CPD 4005015 SUPS	400x500x150	45M (15 x 3 rows)	1
CPD 4006515 SUPS	400x650x150	60M (15 x 4 rows)	1
CPD 4505015 SUPS	450x500x150	51M (17 x 3 rows)	1
CPD 4506515 SUPS	450x650x150	68M (17 x 4 rows)	1