

CURVED SAFETY GLASS DOOR CABINETS

flush mounting

Technical Characteristic



- Usage for installation of electrical instruments
- Easy and Fast Installation
- Wide Space for the Cabling
- Pre-Drilled Entries For an Easy Installation
- Tempered Glass Door
- Thickness is 1.20 mm
- Triangle Lock System



CPD - Flush Mounting -Distribution Cabinets - with mounting plate

Code	Dimension (WxHxD)	DIN Rail Modules	Pack
CPD 4005010 SAM	400x500x100	Mounting Plate	1
CPD 4006510 SAM	400x650x100	Mounting Plate	1
CPD 4505010 SAM	450x500x100	Mounting Plate	1
CPD 4506510 SAM	450x650x100	Mounting Plate	1



CPD - Flush Mounting Distribution Cabinets with Din rail accessory + Blank Cover

Code	Dimension (WxHxD)	DIN Rail Modules	Pack
CPD 4005010 SAPP	400x500x100	30m (15x2 rows)	1
CPD 4006510 SAPP	400x650x100	45M (15x3 rows)	1
CPD 4505010 SAPP	450x500x100	34M (17x2 rows)	1
CPD 4506510 SAPP	450x650x100	51M (17x3 rows)	1



CPD Flush Mounting Distribution Cabinets with Din Rail Accessory

Code	Dimension (WxHxD)	DIN Rail Modules	Pack
CPD 4005010 SAPS	400x500x100	30M (15x2 rows)	1
CPD 4006510 SAPS	400x650x100	45M (15x3 rows)	1
CPD 4505010 SAPS	450x500x100	34M (17x2 rows)	1
CPD 4506510 SAPS	450x650x100	51M (17x3 rows)	1