

# CURVED SAFETY GLASS DOOR CABINETS

flush mounting

## Technical Characteristic



- Usage for installation of electrical instruments
- Easy and Fast Installation
- Wide Space for the Cabling
- Pre-Drilled Entries For an Easy Installation
- Tempered Glass Door
- Thickness is 1.20 mm
- Triangle Lock System



### CPD Flush Mounting Distribution Cabinets with Mounting Plate

Code	Dimension (WxHxD)	DIN Rail Modules	Pack
CPD 6006010 SAM	600x600x100	Mounting Plate	1
CPD 6007510 SAM	600x750x100	Mounting Plate	1
CPD 6009010 SAM	600x900x100	Mounting Plate	1
CPD 6010510 SAM	600x1050x100	Mounting Plate	1



### CPD Flush Mounting Distribution Cabinets with Din Rail Accessory + Blank Cover h : 200mm

Code	Dimension (WxHxD)	DIN Rail Modules	Pack
CPD 6006010 SAPP	600x600x100	66M [22x3 rows]	1
CPD 6007510 SAPP	600x750x100	88M [22x4 rows]	1
CPD 6009010 SAPP	600x900x100	110M [22x5 rows]	1
CPD 6010510 SAPP	600x1050x100	132M [22 x 6 rows]	1



### CPD - Flush Mounting Distribution Cabinets - with Din Rail Accessory

Code	Dimension (WxHxD)	DIN Rail Modules	Pack
CPD 6006010 SAPS	600x600x100	72M [22x4 rows]	1
CPD 6007510 SAPS	600x750x100	110M [22x5 rows]	1
CPD 6009010 SAPS	600x900x100	132M [22x6 rows]	1
CPD 6010510 SAPS	600x1050x100	154M [22x7 rows]	1