

## Limitatori - Gama "LL8XCK" - IP65



COD dablerom	DENUMIRE	PACK. (buc)
33-010	Plastic LL8XCK-P118	1
33-011	Plastic LL8XCK-P145	1
33-012	Plastic LL8XCK-P110	1
33-013	Plastic LL8XCK-P102	1
33-014	Plastic LL8XCK-P108	1
33-015	Plastic LL8XCK-P155	1

- Gama :LL8XCK
- Material :**Plastic**
- Grad de protectie: IP65
- Viteza de actionare : 0.5m-50m/sec.
- Frecventa de actionare : - mecanic: 120act./min.  
- electric: 30act./min.
- Durata de viata : - mecanic > 10.000.000 de actiuni  
- electric > 500.000 de actiuni
- Rezistenta de contact : 25m  $\Omega$
- Rezistenta de izolatie > 100M  $\Omega$  (la 500V DC)
- Temperatura de lucru : -15°C ... +70°C
- Umiditate de lucru <95%RH
- Dimensiuni: L:62mm W:30mm h:32mm

Ui:500V Ith:10A IP65  
Ue:250V Ie:6A AC-15  
Ue:220V Ie:0.3A DC-13  
IEC60947-5-1

**IP65**  
**PLASTIC**



**33-010**  
**LL8XCK-P118**



**33-011**  
**LL8XCK-P145**



**33-012**  
**LL8XCK-P110**



**33-013**  
**LL8XCK-P102**



**33-014**  
**LL8XCK-P108**



**33-015**  
**LL8XCK-P155**

## Limitatori - Gama "D4B" - IP65



COD dablerom	DENUMIRE	PACK. (buc)
33-000	Metalic D4B-1111N	1
33-001	Metalic D4B-1116N	1
33-002	Metalic D4B-1117N	1
33-005	Metalic D4B-1171N	1
33-006	Metalic D4B-1181N	1

- Gama :D4B
- Material :**Metal**
- Grad de protectie: IP65
- Viteza de actionare : 1m-2m/sec.
- Frecventa de actionare : - mecanic: 120act./min.  
- electric: 30act./min.
- Durata de viata : - mecanic > 15.000.000 de actiuni  
- electric > 500.000 de actiuni
- Rezistenta de contact < 25m  $\Omega$
- Rezistenta de izolatie > 100M  $\Omega$  (la 500V DC)
- Temperatura de lucru : -15°C ... +80°C
- Umiditate de lucru <95%RH
- Dimensiuni: L:73mm W:40mm h:41mm

**IP65**  
**METALIC**



**33-000**  
**D4B-1111N**



**33-001**  
**D4B-1116N**



**33-002**  
**D4B-1117N**



**33-005**  
**D4B-1171N**



**33-006**  
**D4B-1181N**