

## Various cable entry push-in and it's done



- cable entry via integrated elastic membranes in box walls for fast cable entry up to degree of protection IP 66



- alternatively, a cable gland can be set after removing the elastic membrane and extension ring



- cable entry through the bottom of the box via integrated elastic membrane

## Modern terminal technology innovative und flexibel



- different terminal positions and mounting options
- up to enclosure size 10 mm<sup>2</sup> two terminal bars can be mounted in one box, even different terminal sizes are possible



- High-positioned terminals offer more space for wiring - as well when connecting the maximum number of conductors
- protected against accidental loosening



- all terminals with two clamping units per pole
- all terminals with two clamping units per pole
- every pole allows the connection of various conductor cross sections and conductor types

## Lots of accessories perfectly included



- external brackets for fastening are always included



- retaining strap prevents the lid from falling or losing and makes daily installation work easier



- closes quickly by a quarter turn, closed position is easily visible
- Easy identification using label as accessories


**DK Cable junction boxes**  
**For normal environment and protected outdoor**  
**Cable entry via integrated elastic membranes or metric knockouts**



**DK 0202 G** NEW  
**1.5-2.5 mm<sup>2</sup>, Cu 3~**

- terminal with 2 clamping units per pole
- 5-pole per pole 8 x 0,75 mm<sup>2</sup> f, 6 x 1,5 mm<sup>2</sup> sol / f, 4 x 2,5 mm<sup>2</sup> sol / f, 2 x 4 mm<sup>2</sup> sol / f
- with integrated elastic membranes, which can be removed for cable entry via cable glands, sealing range 6.0-15.0 mm
- with one cable entry in the bottom, sealing range Ø 6.0-13.0 mm
- lid fasteners sealable without accessories
- retaining strap and external brackets for wall fixing included

IP  
66




rated insulation voltage	U <sub>i</sub> = 690 V a.c./d.c.
current carrying capacity	20 A
tightening torque for terminal	0.5 Nm
material	PP (polypropylene)



**DK 0402 G** NEW  
**1.5-2.5 mm<sup>2</sup>, Cu 3~**

- terminal with 2 clamping units per pole
- 5-pole per pole 8 x 0,75 mm<sup>2</sup> f, 6 x 1,5 mm<sup>2</sup> sol / f, 4 x 2,5 mm<sup>2</sup> sol / f, 2 x 4 mm<sup>2</sup> sol / f
- with elastic membranes, which can be removed for cable entry via cable glands, sealing range 9.0-17.0 mm
- with one cable entry in the bottom, sealing range Ø 6.0-15.0 mm
- lid fasteners sealable without accessories
- retaining strap and external brackets for wall fixing included

IP  
66




rated insulation voltage	U <sub>i</sub> = 690 V a.c./d.c.
current carrying capacity	20 A
tightening torque for terminal	0.5 Nm
material	PP (polypropylene)



**DK 0404 G** NEW  
**1.5-4 mm<sup>2</sup>, Cu 3~**

- terminal with 2 clamping units per pole
- 5-pole per pole 8 x 1,5 mm<sup>2</sup> sol / f, 6 x 2,5 mm<sup>2</sup> sol / f, 4 x 4 mm<sup>2</sup> sol / f, 2 x 6 mm<sup>2</sup> sol / f
- with elastic membranes, which can be removed for cable entry via cable glands, sealing range 9.0-17.0 mm
- with one cable entry in the bottom, sealing range Ø 6.0-15.0 mm
- lid fasteners sealable without accessories
- retaining strap and external brackets for wall fixing included

IP  
66



rated insulation voltage	U <sub>i</sub> = 690 V a.c./d.c.
current carrying capacity	32 A
tightening torque for terminal	0.7 Nm
material	PP (polypropylene)