

12 / 7



Reference table	
Present types	New types
D 9220	DK 0200 R
D 9225	DK 0202 R DK 0402 R
D 9240	DK 0400 R
D 9245	DK 0404 R DK 0604 R

DK Cable junction boxes

for safety lighting circuits,
for equipotential bonding conductors

Cable entry via integrated elastic membranes or metric knockouts

- Cable junction box with red lid for safety lighting circuits
- With elastic membrane, which can be removed for cable entry via cable glands
- Multi-level knockouts for cable glands in different sizes
- Cable entry through the bottom of the box via integrated elastic membrane
- Closes quickly by a quarter turn - locked position well visible (open - locked)
- Lid fasteners sealable without accessories
- External brackets for wall fixing included
- Retaining strap, details see product description
- High-position terminals with more space for wiring
- All terminals with two clamping units per pole
- Every pole allows the connection of various conductor cross sections and conductor types
- Terminals prevent damage of conductors, also with flexible conductors without ferrule
- Different terminal positions and fastening options
- Material: polypropylene or polystyrene
- Burning behaviour: glow wire test in accordance with IEC 60695-2-11: 750 °C, flame-retardant, self-extinguishing
- Colour: grey RAL 7035, with red lid RAL 3000
- Terminal box for equipotential bonding cables

DK Cable junction boxes
For safety lighting circuits
Cable entry via integrated elastic membranes or metric knockouts




DK 0202 R NEW
1.5-2.5 mm², Cu 3~

- terminal with 2 clamping units per pole
- 5-pole per pole 8 x 0,75 mm² f, 6 x 1,5 mm² sol / f, 4 x 2,5 mm² sol / f, 2 x 4 mm² sol / f
- with red lid RAL 3000
- for safety lighting circuits
- with integrated elastic membranes, which can be removed for cable entry via cable glands, sealing range 6.0-15.0 mm
- with one cable entry in the bottom, sealing range Ø 6.0-13.0 mm
- lid fasteners sealable without accessories
- retaining strap and external brackets for wall fixing included

rated insulation voltage	U _i = 690 V a.c./d.c.
current carrying capacity	20 A
tightening torque for terminal material	0.5 Nm
material	PP (polypropylene)

IP
66




DK 0402 R NEW
1.5-2.5 mm², Cu 3~

- terminal with 2 clamping units per pole
- 5-pole per pole 8 x 0,75 mm² f, 6 x 1,5 mm² sol / f, 4 x 2,5 mm² sol / f, 2 x 4 mm² sol / f
- with red lid RAL 3000
- for safety lighting circuits
- with elastic membranes, which can be removed for cable entry via cable glands, sealing range 9.0-17.0 mm
- with one cable entry in the bottom, sealing range Ø 6.0-15.0 mm
- lid fasteners sealable without accessories
- retaining strap and external brackets for wall fixing included

rated insulation voltage	U _i = 690 V a.c./d.c.
current carrying capacity	20 A
tightening torque for terminal material	0.5 Nm
material	PP (polypropylene)

IP
66



DK 0404 R NEW
1.5-4 mm², Cu 3~

- terminal with 2 clamping units per pole
- 5-pole per pole 8 x 1,5 mm² sol / f, 6 x 2,5 mm² sol / f, 4 x 4 mm² sol / f, 2 x 6 mm² sol / f
- with red lid RAL 3000
- for safety lighting circuits
- with elastic membranes, which can be removed for cable entry via cable glands, sealing range 9.0-17.0 mm
- with one cable entry in the bottom, sealing range Ø 6.0-15.0 mm
- lid fasteners sealable without accessories
- retaining strap and external brackets for wall fixing included

rated insulation voltage	U _i = 690 V a.c./d.c.
current carrying capacity	32 A
tightening torque for terminal material	0.7 Nm
material	PP (polypropylene)

IP
66

