



EM31



PW




tip type	descriere description	date tehnice technical data	mărime size	culoare colour	
EM12	VARIATOR ROTATIV/CAP SCARĂ DIMMER ROTATIVE 2WAY	RL 300W	1M	<input type="checkbox"/> PW alb polar white <input type="checkbox"/> MW alb mat matte white <input type="checkbox"/> SB negru mat soft touch black <input type="checkbox"/> AT antracit anthracite <input type="checkbox"/> ES argintiu elox silver <input type="checkbox"/> IW fildes ivory white	<input type="checkbox"/> BL albastru blue <input type="checkbox"/> RD roșu red <input type="checkbox"/> GR verde green <input type="checkbox"/> OR portocaliu orange <input type="checkbox"/> RG roșu/verde red/green
EM23	VARIATOR ÎNCORPORAT DIMMER INBOX	R (250 W), (RC,RL 200VA)	/		
.	.	.	.		
.	.	.	.		

VARIATOR ROTATIV/CAP SCARĂ RL 300W 1M



- EM12PW
- EM12MW
- EM12SB
- EM12AT
- EM12ES
- EM12IW

- control rotativ cu întrerupător cap scară
- sarcină RL, 40W - 300W
- tensiune de alimentare 230V~ 50Hz
- se poate combina cu întrerupător cap scară
- instalarea mai multor dispozitive într-o singură doză este permisă doar dacă sarcina lor maximă totală nu depășește puterea maximă a unui singur variator
- un circuit permite utilizarea unui singur variator
- fără siguranță încorporată - trebuie să se utilizeze siguranță externă
- în conformitate cu EN 60669-1
- borne cu șurub - 1,5-2,5mm²
- indicare LED integrată a nivelului de variere



DIMMER ROTATIVE/2WAY RL 300W 1M


- rotation control with 2-way switch
- load RL, 40W - 300W
- supply voltage 230V~ 50Hz
- 2-way switch combination is possible
- installing several devices together in one box is only permitted if their total maximum load does not exceed the maximum power of a single dimmer
- one circuit allows the use of only one dimmer
- no built-in fuse - external fuse must be used
- in accordance with EN 60669-1
- screw contacts - 1.5-2.5mm²
- integrated LED indication of dimming level

VARIATOR ROTATIV/CAP SCARĂ LED 60W 1M



- EM13PW
- EM13MW
- EM13SB
- EM13AT
- EM13ES
- EM13IW

- control rotativ cu întrerupător cap scară
- sarcini:
LED, 0 - 60W (max. 6 becuri LED cu intensitate variabilă)
GLS, 0 - 60W
- tensiune de alimentare 230V~ 50Hz
- se poate combina cu întrerupător cap scară
- instalarea mai multor dispozitive într-o singură doză este permisă doar dacă sarcina totală maximă nu depășește puterea maximă a unui singur variator
- un circuit permite utilizarea unui singur variator
- fără siguranță încorporată - trebuie să se utilizeze siguranță externă
- în conformitate cu IEC60669-2-1
- borne cu șurub - 1,5-2,5mm²



DIMMER ROTATIVE/2WAY LED 60W 1M

- rotation control with 2-way switch
- loads: LED, 0 - 60W (max. 6 dimmable LED lamps)
GLS, 0 - 60W
- supply voltage 230V~ 50Hz
- 2-way switch combination is possible
- installing several devices together in one box is only permitted if their total maximum load does not exceed the maximum power of a single dimmer
- one circuit allows the use of only one dimmer
- no built-in fuse - external fuse must be used
- in accordance with IEC60669-2-1
- screw contacts - 1.5-2.5mm²