



WITH FUNCTION OF SIGNALISATION OF LIGHTING SWITCHING OFF

AS-221T

Turned ON staircase timer supports the lighting during set time by potentiometer (from 0.5 min. to 10 min.) and upon elapse of this set time a reduction by half of lighting brightness follows for about 30 seconds, after that OFF follows (thus an occurrence of a sudden darkness is avoided, enabling safe approach to the switch). After switching OFF the lighting there is possibility to switch it ON again.



power supply	230V AC
load current	<10A
switching OFF delay - adjustable	0.5÷10min.
time of reduced brightness	30sec
switching ON delay	<1sec
power consumption	0.8W
terminal	2.5mm ² screw terminals
working temperature	-25÷50°C
dimensions	2 modules (35mm)
mounting	on TH-35 rail
protection level	IP20


ATTENTION!

The AS-221T is not compatible with LED lamps, glow-discharge tubes, compact fluorescent lamps and other lighting devices including electric starters.

AS-222T

WITH COUNTER BLOCKADE

Turned ON staircase timer supports the lighting during set time by potentiometer (from 0.5 min. to 10 min.) and upon elapse of this set time a reduction by half of lighting brightness follows for about 30 seconds, after that OFF follows (thus an occurrence of a sudden darkness is avoided, enabling safe approach to the switch). After switching OFF the lighting there is possibility to switch it ON again. Function of counter blockade does not allow to keep the light-ON in case of staircase switch blocking (after blocking the pushbutton, for example by match, the timer will count the set time and switch OFF the lighting). Next switching ON can be after removing the blockade.



power supply	230V AC
load current	<10A
switching OFF delay - adjustable	0.5÷10min.
time of reduced brightness	30sec
switching ON delay	<1sec
terminal	2.5mm ² screw terminals
power consumption	0.8W
working temperature	-25÷50°C
dimensions	2 modules (35mm)
mounting	on TH-35 rail
protection level	IP20

ATTENTION!

The AS-222T is not compatible with LED lamps, glow-discharge tubes, compact fluorescent lamps and other lighting devices including electric starters.

ATTENTION!

Automatic staircase switches for other voltages than specified in the technical data table are also available on special request (12 V, 48 V and 110 V AC/DC and other). The offer does not include the AS-221T and AS-222T models.