


Other tapes

- textile, marking and reflective tapes also available
- self-amalgamating tapes: material rubber or silicone
- universal DUCT TAPE: strong, high adhesion, water-tightness
- reflective tapes: increase biker, pedestrian and pram safety
- double-sided acrylic tapes: high adhesion and flexibility

tape type: asphalt textile tape = width: 15 mm = length: 15 m = thickness: 0.4 mm = electric strength - minimum: 1 kV/mm = recommended storage temperature: -5 °C to +40 °C = operating temperature range: 5-40 °C = UV resistant = adhesive material: asphalt = integrated textile mesh = dimensions: 80 × 17 mm = packaging: 1 pc, PVC hanging




F6515

1/-/-/60

20 02 151 520

15/15 CERNA

tape type: asphalt textile tape = width: 19 mm = length: 10 m = thickness: 0.4 mm = electric strength - minimum: 1 kV/mm = recommended storage temperature: -5 °C to +40 °C = operating temperature range: 5-40 °C = UV resistant = adhesive material: asphalt = integrated textile mesh = dimensions: 70 × 17 mm = packaging: 1 pc, PVC hanging




F6910

1/-/-/60

20 02 191 020

19/10 CERNA

tape type: self-amalgamating tape = width: 19 mm = length: 10 m = thickness: 0.76 mm = electric strength - minimum: 14 kV/mm = recommended storage temperature: -20 °C to +80 °C = operating temperature range: 5-95 °C = adhesive material: rubber = intended use: sealing, repairs = dimensions: 120 × 20 mm = packaging: 1 pc, paper box




F51912

1/-/5/30

20 03 191 020

19/10
SELFFUSING

tape type: self-amalgamating tape = width: 25 mm = length: 5 m = thickness: 0.76 mm = electric strength - minimum: 14 kV/mm = recommended storage temperature: -20 °C to +80 °C = operating temperature range: 5-95 °C = adhesive material: rubber = intended use: sealing, repairs = dimensions: 95 × 28 mm = packaging: 1 pc, paper box



F52502

1/-/5/30

20 03 250 520

25/5 SELFFUSING