




tape type: LDPE (low-density polyethylene) warning tape = width: 75 mm = length: 250 m = thickness: 0.03 mm = recommended storage temperature: 5-30 °C = installation temperature range: 5-30 °C = UV resistant = intended use: border of excavations, demarcation of building spaces, sports tracks, various dangerous locations = dimensions: 140 × 75 mm = packaging: 1 pc, paper unwinding mechanism




F87525 1/-/-/18
20 04 752 500 75/250 BARRIER

tape type: acrylic double-sided tape = width: 12 mm = length: 3 m = thickness: 1.00 mm = recommended storage temperature: 5-40 °C = installation temperature range: 5-40 °C = UV resistant = adhesive material: acrylic = intended use: hobby, workshop, garden = dimensions: 88 × 12 mm = packaging: 1 pc, blister



F6060 1/-/10/60
20 06 000 000 12/3 ACRYL

tape type: acrylic double-sided tape = width: 18 mm = length: 3 m = thickness: 1.00 mm = recommended storage temperature: 5-40 °C = installation temperature range: 5-40 °C = UV resistant = adhesive material: acrylic = intended use: hobby, workshop, garden = dimensions: 88 × 18 mm = packaging: 1 pc, blister



F6080 1/-/10/60
20 06 000 010 18/3 ACRYL

tape type: reflexive safety tape = width: 25 mm = length: 2 m = thickness: 0.19 mm = recommended storage temperature: -20 °C to +80 °C = installation temperature range: -25-90 °C = UV resistant = adhesive material: rubber = intended use: hobby, cycling, safety element = dimensions: 53 × 53 × 25 mm = packaging: 12 pcs, display box



F6070 12/-/-/216
20 05 000 010 25/2 REFLEX TAPE