



- tape type: PVC
- width: 15 mm
- length: 10 m
- thickness: 0.13 mm
- electric strength - minimum: 40 kV/mm
- flame tests: less than 1 second
- recommended storage temperature: 10-45 °C
- operating temperature range: -25-90 °C
- ROHS compliant




- REACH compliant
- UV resistant
- adhesive material: rubber
- intended use: cable insulation
- dimensions: 60 × 15 mm
- packaging: 10 pcs, foil



F61515 10/10/-/360
20 01 151 050 15/10 ZEL/ZLUTA

- tape type: PVC
- width: 15 mm
- length: 10 m
- thickness: 0.13 mm
- electric strength - minimum: 40 kV/mm
- flame tests: less than 1 second
- recommended storage temperature: 10-45 °C
- operating temperature range: -25-90 °C
- ROHS compliant




- REACH compliant
- UV resistant
- adhesive material: rubber
- intended use: cable insulation
- dimensions: 60 × 15 mm
- packaging: 10 pcs, foil



F61516 10/10/-/360
20 01 151 060 15/10 ZLUTA

- tape type: PVC
- width: 15 mm
- length: 10 m
- thickness: 0.13 mm
- electric strength - minimum: 40 kV/mm
- flame tests: less than 1 second
- recommended storage temperature: 10-45 °C
- operating temperature range: -25-90 °C
- ROHS compliant



- REACH compliant
- UV resistant
- adhesive material: rubber
- intended use: cable insulation
- dimensions: 60 × 15 mm
- packaging: 10 pcs, foil



F61517 10/10/-/360
20 01 151 070 15/10 HNEDA

- tape type: PVC
- width: 15 mm
- length: 10 m
- thickness: 0.13 mm
- electric strength - minimum: 40 kV/mm
- flame tests: less than 1 second
- recommended storage temperature: 10-45 °C
- operating temperature range: -25-90 °C
- ROHS compliant



- REACH compliant
- UV resistant
- adhesive material: rubber
- intended use: cable insulation
- dimensions: 60 × 15 mm
- packaging: 1 pc, foil



F61519 10/10/-/360
20 01 151 090 15/10 GREEN

- tape type: PVC
- width: 15 mm
- length: 10 m
- thickness: 0.13 mm
- electric strength - minimum: 40 kV/mm
- flame tests: less than 1 second
- recommended storage temperature: 10-45 °C
- operating temperature range: -25-90 °C
- ROHS compliant



- REACH compliant
- UV resistant
- adhesive material: rubber
- intended use: cable insulation
- dimensions: 60 × 150 mm
- packaging: 10 pcs, foil



F615992 1/-/-/36
20 01 151 092 15/10 COLOR MIX