

A5201 1/-/-/500
31 47 020 010 HR5 CU



- product: soldering tip copper for solderi
- number of soldering tips: 5
- packaging: 1 pc, PVC packet



A5301 1/-/-/500
31 47 030 010 KLF 16G



- product: rosin for soldering
- packaging: 1 pc, PVC packet



A5401 1/-/-/500
31 47 040 010 CN 1,5 10G



- product: tube lead-free solder filled wit
- packaging: 1 pc, PVC packet



Tapes

Electroinsulating PVC tapes

- width: 15–25 mm, length: 10–20 m, thickness: 0.13 mm
- white, red, black, brown, blue, green, yellow or mix
- meets ROHS and REACH (certification for automotive industry)
- adhesion 1.5 N/10 mm², dielectric strength 40 kV/mm²

- tape type: PVC
- width: 19 mm
- length: 10 m
- thickness: 0.13 mm
- electric strength - minimum: 40 kV/mm
- flame tests: less than 1 second
- recommended storage temperature: 10–45 °C
- operating temperature range: -25–90 °C
- ROHS compliant

- REACH compliant
- UV resistant
- adhesive material: rubber
- intended use: cable insulation
- dimensions: 60 × 20 mm
- packaging: 10 pcs, foil



F61912 10/10/-/300
20 01 191 020 19/10 CERNA