



- tape type: PVC
- width: 19 mm
- length: 20 m
- thickness: 0.13 mm
- electric strength - minimum: 40 kV/mm
- flame tests: less than 1 second
- recommended storage temperature: 10-45 °C
- operating temperature range: -25-90 °C
- ROHS compliant



- REACH compliant
- UV resistant
- adhesive material: rubber
- intended use: cable insulation
- dimensions: 70 × 20 mm
- packaging: 10 pcs, foil



F61921 10/10/-/200
20 01 192 010 19/20 BILA

- tape type: PVC
- width: 19 mm
- length: 20 m
- thickness: 0.13 mm
- electric strength - minimum: 40 kV/mm
- flame tests: less than 1 second
- recommended storage temperature: 10-45 °C
- operating temperature range: -25-90 °C
- ROHS compliant



- REACH compliant
- UV resistant
- adhesive material: rubber
- intended use: cable insulation
- dimensions: 70 × 20 mm
- packaging: 10 pcs, foil



F61922 10/-/-/200
20 01 192 020 19/20 CERNA

- tape type: PVC
- width: 19 mm
- length: 20 m
- thickness: 0.13 mm
- electric strength - minimum: 40 kV/mm
- flame tests: less than 1 second
- recommended storage temperature: 10-45 °C
- operating temperature range: -25-90 °C
- ROHS compliant




- REACH compliant
- UV resistant
- adhesive material: rubber
- intended use: cable insulation
- dimensions: 70 × 20 mm
- packaging: 10 pcs, foil



F61923 10/10/-/200
20 01 192 030 19/20 CERVENA

- tape type: PVC
- width: 19 mm
- length: 20 m
- thickness: 0.13 mm
- electric strength - minimum: 40 kV/mm
- flame tests: less than 1 second
- recommended storage temperature: 10-45 °C
- operating temperature range: -25-90 °C
- ROHS compliant




- REACH compliant
- UV resistant
- adhesive material: rubber
- intended use: cable insulation
- dimensions: 70 × 20 mm
- packaging: 10 pcs, foil



F61924 10/10/-/200
20 01 192 040 19/20 MODRA

- tape type: PVC
- width: 19 mm
- length: 20 m
- thickness: 0.13 mm
- electric strength - minimum: 40 kV/mm
- flame tests: less than 1 second
- recommended storage temperature: 10-45 °C
- operating temperature range: -25-90 °C
- ROHS compliant



- REACH compliant
- UV resistant
- adhesive material: rubber
- intended use: cable insulation
- dimensions: 70 × 20 mm
- packaging: 10 pcs, foil



F61925 10/10/-/200
20 01 192 050 19/20 ZEL/ZLUTA