



tape type: silicone vulcanisation = width: 25 mm = length: 3 m = thickness: 0.60 mm = electric strength - minimum: 8 kV/mm = flame tests: less than 1 second = operating temperature range: -60-260 °C = UV resistant = creates pressure-tight joint = intended use: hobby, workshop, garden, repair in vehicle engine compartment, emergency repair of pipes, hoses = dimensions: 60 × 30 mm = packaging: 1 pc, blister



**F52503** 1/20/-/80  
20 03 250 320 25/3 SILICONE

tape type: universal adhesive DUCT TAPE = width: 48 mm = length: 10 m = thickness: 0.21 mm = recommended storage temperature: -20 °C to +80 °C = operating temperature range: 5-80 °C = UV resistant = adhesive material: synthetic rubber = intended use: hobby, workshop, garden = integrated textile mesh: 70 fibers = dimensions: 105 × 48 mm = packaging: 10 pcs, display box



**F6030** 10/-/-/60  
20 02 502 002 48/10 UNITAPE

tape type: LDPE (low-density polyethylene) warning tape = width: 75 mm = length: 250 m = thickness: 0.03 mm = recommended storage temperature: 5-30 °C = operating temperature range: 5-30 °C = UV resistant = intended use: border of excavations, demarcation of building spaces, sports tracks, various dangerous locations = dimensions: 140 × 75 mm = packaging: 1 pc, paper unwinding mechanism



**F87525** 1/-/-/18  
20 04 752 500 75/250 BARRIER

tape type: acrylic double-sided tape = width: 12 mm = length: 3 m = thickness: 1.00 mm = recommended storage temperature: 5-40 °C = operating temperature range: 5-40 °C = UV resistant = adhesive material: acrylic = intended use: hobby, workshop, garden = dimensions: 88 × 12 mm = packaging: 1 pc, blister



**F6060** 1/-/10/60  
20 06 000 000 12/3 ACRYL

tape type: acrylic double-sided tape = width: 18 mm = length: 3 m = thickness: 1.00 mm = recommended storage temperature: 5-40 °C = operating temperature range: 5-40 °C = UV resistant = adhesive material: acrylic = intended use: hobby, workshop, garden = dimensions: 88 × 18 mm = packaging: 1 pc, blister



**F6080** 1/-/10/60  
20 06 000 010 18/3 ACRYL