

TED 15KVA / 20KVA / 30KVA cu servomotor

CARACTERISTICI

- culori: alb
- carcasa metalica
- 4x rotile pentru manipulare/ transportare usoara
- switch bypass manual
- delay selectabil: 6s/180s
- display digital: INPUT | OUTPUT VOLTAGE | OUTPUT CURRENT
- aplicatii: centrala termica, electronice, electrocasnice mici/medii/mari, scule electrice

PROTECTIE

- protectie la suprasarcina, supraincalzire, supratensiune si scurt-circuit
- alarma sonora
- clasa de izolare electrica: IP20



APLICATII



SPECIFICATII TEHNICE

	OPTIUNEA 15KVA	OPTIUNEA 20KVA	OPTIUNEA 30KVA
Putere	12000W	16000W	24000W
Tensiune / Frecventa intrare		160-260V / 45-65Hz	
Tensiune / Frecventa iesire		220V AC / 50Hz	
Precizie la iesire		+/- 1-3%	
Unda		sinusoidala pura	
Eficienta / Timp de raspuns		90-99% / < 1s	
Capacitate suprasarcina		180s - 120% / 30s - 150% / 10s - 200% / 5s - 300%	
Conectori intrare / iesire		Bloc terminal (intrare) / Bloc terminal (iesire)	
Dimensiuni (L x l x i)	565 x 333 x 525 mm		575 x 333 x 645 mm
Greutate	78kg	100kg	108kg
Temperatura functionare		0°C pana la 40°C	
Umiditate functionare		0-90% fara condens	
Cod produs	DZ083487	DZ085359	GN086037