

**PROTECTION - WHITE VERSION**

**MINIATURE CIRCUIT BREAKERS**



GW 10 463

**MCB - MINIATURE CIRCUIT BREAKERS - C CHARACTERISTIC - 230V AC**

Code	Description	Rated current (A)	Breaking capacity	No. Chorus modules	Pack Carton
GW 10 461	Single pole (1P)	6	3 kA	1	1/12
GW 10 462	Single pole (1P)	10	3 kA	1	1/12
GW 10 463	Single pole (1P)	16	3 kA	1	1/12
GW 10 466	Two-pole (1P+N)	6	3 kA	1	1/12
GW 10 467	Two-pole (1P+N)	10	3 kA	1	1/12
GW 10 468	Two-pole (1P+N)	16	3 kA	1	1/12

DOMESTIC RANGES



GW 10 488

**RCBO - RESIDUAL CURRENT BREAKERS WITH OVERCURRENT PROTECTION - C CHARACTERISTIC - CLASS A - 230V AC - 50/60 HZ**

Code	Description	Rated current (A)	Breaking capacity	Idn	No. Chorus modules	Pack Carton
GW 10 482	Two-pole (1P+N)	6	3 kA	10 mA	2	1/6
GW 10 483	Two-pole (1P+N)	6	3 kA	30 mA	2	1/6
GW 10 485	Two-pole (1P+N)	10	3 kA	10 mA	2	1/6
GW 10 486	Two-pole (1P+N)	10	3 kA	30 mA	2	1/6
GW 10 488	Two-pole (1P+N)	16	3 kA	10 mA	2	1/6
GW 10 489	Two-pole (1P+N)	16	3 kA	30 mA	2	1/6

**PROTECTION DEVICES**



GW 10 491

**FUSE HOLDER - 250V AC**

Code	Rated current (A)	Fuse type	No. Chorus modules	Pack Carton
GW 10 491	16	Ø 6.3x32 mm	1	1/12

**CHARACTERISTICS:** fuse not included.



GW 10 492

**SURGE PROTECTION DEVICE - 230V AC**

Code	Uc	Up	No. Chorus modules	Pack Carton
GW 10 492	275 V ac 50/60Hz	1 kV	1	1/12

**CHARACTERISTICS:** green LED for status signalling.

**APPLICATIONS:** protection of electronic devices (TV, HI-FI, computer, etc.) from overvoltage (resulting from atmospheric conditions or manoeuvres) that could be channelled from the power supply lines.