

TECHNOPOLYMER - WOOD FINISH



GW 16 222 LA

LUX INTERNATIONAL - MAPLE

Code	Description	Type	Centre distance	Pack Carton
GW 16 222 LA	2 gang			12
GW 16 223 LA	2+2 gang	Horizontal	71 mm	6
GW 16 224 LA	2+2 gang	Vertical	71 mm	6
GW 16 226 LA	2+2+2 gang	Horizontal	71 mm	1
GW 16 227 LA	2+2+2 gang	Vertical	71 mm	1
GW 16 228 LA	2+2+2+2 gang	Horizontal	71 mm	1
GW 16 229 LA	2+2+2+2 gang	Vertical	71 mm	1



GW 16 222 LW

LUX INTERNATIONAL - WENGÉ

Code	Description	Type	Centre distance	Pack Carton
GW 16 222 LW	2 gang			12
GW 16 223 LW	2+2 gang	Horizontal	71 mm	6
GW 16 224 LW	2+2 gang	Vertical	71 mm	6
GW 16 226 LW	2+2+2 gang	Horizontal	71 mm	1
GW 16 227 LW	2+2+2 gang	Vertical	71 mm	1
GW 16 228 LW	2+2+2+2 gang	Horizontal	71 mm	1
GW 16 229 LW	2+2+2+2 gang	Vertical	71 mm	1



GW 16 222 LC

LUX INTERNATIONAL - CHERRY

Code	Description	Type	Centre distance	Pack Carton
GW 16 222 LC	2 gang			12
GW 16 223 LC	2+2 gang	Horizontal	71 mm	6
GW 16 224 LC	2+2 gang	Vertical	71 mm	6
GW 16 226 LC	2+2+2 gang	Horizontal	71 mm	1
GW 16 227 LC	2+2+2 gang	Vertical	71 mm	1
GW 16 228 LC	2+2+2+2 gang	Horizontal	71 mm	1
GW 16 229 LC	2+2+2+2 gang	Vertical	71 mm	1

Chorus

THE SHAPES OF BEAUTY



ONE, GEO, LUX, ART, ICE and ICE Touch are the plates for the Gewiss CHORUS innovative domestic range: six different forms reflecting the character, personality and style of those who live in the home. With full spontaneity of gestures and the simplicity of the commands.

ALL THE BENEFITS OF A SINGLE FRAME



One single support (rectangular and square) compatible with all the plates of the Chorus range, without any need for additional adapters. The front coupling on the devices means quick, easy assembly and release without needing to remove the frame.

ERGONOMICS AND DESIGN



The wide range of component customisation possibilities, in terms of colour and modularity, guarantees a wealth of design and ergonomic solutions for every context. Four different colours, three different finishes: glossy white and ivory, satin black and painted titanium guarantee the perfect combination of component and plate.


DOMESTIC RANGES

General characteristics

TECHNICAL DATA AND REFERENCE STANDARDS							
Component	Reference standards	Essential electrical data*			Prolonged operation (no. of position changes)	Resistance to abnormal heat and fire	
		Resistance at test voltage (V)	Insulation resistance (MΩ)	Breaking capacity or category of use		Thermo-pressure with ball (°C)	Glow Wire Test (°C)
Commands	EN 60669-1	2000 at 50 Hz for 1 minute	> 5	1.25 In (200 position changes)	40,000 at In 250V~ cosφ = 0.6	125	850
Italian Std. socket-outlets	IEC 60884-1			1.25 In (100 position changes)	10,000 at In 250V~ cosφ = 0.8		
International Std. socket-outlets	IEC 60884-1			1.25 In (100 position changes)	10,000 at In 250V~ cosφ = 0.8		
Latching relays	EN 60669-1 / EN 60669-2-2				40,000 at In 250V~ cosφ = 0.6		
Momentary relays	EN 60669-1 / EN 60669-2-2		2** ÷ 5	1.25 In (200 position changes)			
Miniature circuit breakers	EN 60898-1			3KA	8,000		
Residual current circuit breakers	EN 61009-1 / EN 61008-1			3KA	4,000		
Supports and plates	EN 60669-1	-	-	-	-	70	650

* For rated voltages and currents, see the specifications for the individual codes. ** The value of 2 MΩ refers to a special condition established by the Standards given alongside.


Characteristics of screw terminals



The terminals, located in the rear part of the devices, are manoeuvrable even after coupling the component to the support, and are suitable for both flexible and rigid cables. The components are supplied with the screws of the terminals open, to reduce wiring times.

TECHNICAL DATA			
Terminal grip on cable traction			>50N
TERMINAL TIGHTENING CAPACITY			
Stranded wires		Solid wires	
Minimum 0.75 mm ²	Maximum 2x4 mm ²	Minimum 0.5 mm ²	Maximum 2x2.5 mm ²

Characteristics of spring terminals (quick wiring)



The spring terminals allow you to carry out the wiring in a shorter time, and without using screwdrivers or other tools. To insert the cable, it is necessary to press the orange lever (opening of terminal). Releasing the lever, the terminal closes automatically, firmly blocking the cable.





TECHNICAL DATA			
Terminal grip on cable traction			>50N
TERMINAL TIGHTENING CAPACITY			
Stranded wires		Solid wires	
Minimum 0.75 mm ²	Maximum 2x4 mm ²	Minimum 0.5 mm ²	Maximum 2x2.5 mm ²

Combination of modular devices and plates

Plates		Modular devices						
		Conventional commands	Electronic push-buttons	Touch commands	Socket-outlets / other devices	Touch command modules		
						Conventional	KNX	KNX with interchangeable symbols
								
ONE		✓	✓	✓	✓	-	-	-
GEO		✓	✓	✓	✓	-	-	-
LUX		✓	✓	✓	✓	-	-	-
ART		✓	✓	✓	✓	-	-	-
ICE	ICE		✓	✓	✓	-	-	-
	ICE Touch (1, 2 or 3 printed symbols)		-	-	-	✓	-	-
	ICE Touch KNX (2, 4 or 6 printed symbols)		-	-	-	-	✓	-
	ICE Touch KNX		-	-	-	-	-	✓

DOMESTIC RANGES

LUX PLATES



LUX INTERNATIONAL PLATES

