

SPECIAL ENCLOSURES

COMBI-DIN - PROTECTED DIN-SYSTEM COMBINED ENCLOSURES



GW 27 071

PROTECTED ENCLOSURES FOR COMBINED INSTALLATION OF DIN MODULAR DEVICES AND SYSTEM SMOKED TRANSPARENT DOOR - GREY RAL 7035 - IP40



Code	No. DIN modules	No. SYSTEM modules	Configuration	Dispersible power (W)	No. knockout holes Ø23	Outer dim. LxHxD (mm)	Characteristics	Pack Carton
GW 27 071	2	4	Module 2 x 2	13	10 on sides / 2 on the bottom	132x132x95	Halogen free	1/8
GW 27 072	4	8	Module 2 x 4	15	12 on sides / 2 on the bottom	231x132x95	Halogen free	1/6
GW 27 073	8	16	Module 4 x 4	18	18 on sides / 2 on the bottom	429x132x95	Halogen free	1/4

CHARACTERISTICS: customized to be divided into 2 vertical compartments (except for GW27071) using the special functional dividers. Knockout holes removable with tool. Enclosures are customized for fixing the earth terminal GW26407. Complete insulation can be obtained by using the screwcaps GW44622.

ACCESSORIES SUPPLIED: quick entry cable gland for cables with Ø from 4 to 14 mm and conduits Ø 16 and 20 mm.

NOTES: dispersible power calculated according to IEC 60670-24.

COMBI-IN - FLUSH-MOUNTING FLANGED COMPONENTS




GW 27 401

SYSTEM 2-GANG WATERTIGHT CAP - GREY RAL 7035 - IP55

Code	No. SYSTEM modules	Door type	Dimensions LxH (mm)	Pack Carton
GW 27 401	2	With membrane	75x85	3/60

ACCESSORIES SUPPLIED: 4 self-tapping screws. IP55 with door closed.

APPLICATIONS: for Q-DIN boards, junction boxes PTC, flanged lids 66 range, Q-BOX and panels



GW 27 403

SYSTEM 2-GANG WATERTIGHT CAP - SOLID SMOKED TRANSPARENT DOOR - GREY RAL 7035 - IP65

Code	No. SYSTEM modules	Door type	Dimensions LxH (mm)	Pack Carton
GW 27 403	2	Rigid IK09	75x85	3/60

ACCESSORIES SUPPLIED: 4 self-tapping screws. IP65 with door closed.

APPLICATIONS: for Q-DIN boards, junction boxes, PTC, flanged lids 66 range, Q-BOX and panels.



GW 22 451

SELF-SUPPORTING WATERTIGHT PLATES FOR INSTALLATION ON FLUSH-MOUNTING RECTANGULAR BOXES - IP55

Code	Description	Colour Plate	For flush mounting box	Pack Carton
GW 22 451	3 gang	Cloud white	GW24403, GW24403PM	30
GW 22 452	3 gang	Black	GW24403, GW24403PM	30
GW 22 453	3 gang	Grey RAL 7035	GW24403, GW24403PM	30
GW 22 461	4 gang	Cloud white	GW24404, GW24404PM	30
GW 22 462	4 gang	Black	GW24404, GW24404PM	30
GW 22 463	4 gang	Grey RAL 7035	GW24404, GW24404PM	30

CHARACTERISTICS: ergonomic membrane with notches in UV-resistant material. Snap closing system. Opening made easy by wide key.