



GW 27 431 B

**INFRARED ADJUSTABLE MOTION DETECTOR 230V - 50 HZ - IP55**

| Code        | Range of action | Duration adjustment | Threshold adjustment | Outer dim. LxHxD (mm) | Pack Carton |
|-------------|-----------------|---------------------|----------------------|-----------------------|-------------|
| GW 27 431 B | 12 m            | 10 sec. - 12 min.   | 3 - 100 lux          | 72x88x106             | 1/10        |

**CHARACTERISTICS:** horizontal cover range: 240°; rotating angle of the horizontal detection head: ±90°; sensitivity regulation: 3-12m. Incandescent and halogen lamps: max. 2000W, uncompensated fluorescent lamps: max. 480W, compensated fluorescent lamps: max. 200W, dimmable LED lamps 230V ac and dimmable CFL lamps: max. 8 (7÷23W).

**ACCESSORIES SUPPLIED:** support for installation in corners; cover kit for limiting the detection field.



GW 27 432

**LIGHT-SENSITIVE DETECTOR WITH RELAY OUTPUT 230V - 50/60 HZ - IP65**

| Code      | Threshold adjustment | Output contacts         | Outer dim. LxHxD (mm) | Pack Carton |
|-----------|----------------------|-------------------------|-----------------------|-------------|
| GW 27 432 | 0 - 200 lux          | 1NO 16 A (AC1) 250 V ac | 55x106x45             | 1/24        |

**CHARACTERISTICS:** halogen and incandescent lamps: 23x100W (2300W); uncompensated fluorescent lamps: 12x58W (700W); compensated fluorescent lamps: 5x58W 35uF (290W); LED and energy saving lamps: max. 7 (7÷15W).

**APPLICATIONS:** wall or pole mounting.