

METALLISED TECHNOPOLYMER



GW 32 073

PLAYBUS - SOFT CHROME, GLOSSY FINISH

Code	Description	Configuration	For support codes	Pack Carton
GW 32 072	2 gang		GW32402	48
GW 32 073	3 gang		GW32403	48
GW 32 074	4 gang		GW32404	24
GW 32 076	6 gang		GW32406	24
GW 32 077	4+4 gang	Overlapping	GW32407	12



GW 32 063

PLAYBUS - ANTIQUE GOLD, GLOSSY FINISH

Code	Description	Configuration	For support codes	Pack Carton
GW 32 062	2 gang		GW32402	48
GW 32 063	3 gang		GW32403	48
GW 32 064	4 gang		GW32404	24
GW 32 066	6 gang		GW32406	24
GW 32 067	4+4 gang	Overlapping	GW32407	12

Playbus



DESIGN AND SAFETY




The range includes plates in 6 colours and two different shapes (modern or classic), with a glossy or satin finish. The use of technopolymer ensures the total safety of the electrical insulation, and a longer lifespan for the colours and finishes.

COMMAND DEVICES



The command devices have three types of back-lighting: functional (visible also during the day), night-time localisation (moderate light) and iconographical (with symbols).

INSTALLATION FLEXIBILITY



With the Playbus range you can manage several socket-outlets and several lines from just one point, thanks to the high-capacity plates (up to 18 modules) with internal circuit separation. Moreover, the high degree of installation flexibility is guaranteed by the wide range of accessories available.

General characteristics

Modular range of devices for domestic and similar uses on frames for flush-mounting boxes of up to 18 modules. It includes controls, socket-outlets, protections, indicators, connectors and a vast range of electronic components for domotics and special services. There are also boxes and plates for surface-mounting and free-standing applications.

TECHNICAL DATA AND REFERENCE STANDARDS


































Component	Reference standards	Essential electrical data*			Prolonged operation (no. position changes)	Resistance to abnormal heat and fire	
		Resistance at test voltage (V)	Insulation resistance (MΩ)	Breaking capacity or category of use		Thermo-pressure with ball (°C)	Glow Wire Test (°C)
Commands	EN 60669-1	2000 at 50 Hz for 1 minute	> 5	1,25 In (200 position changes)	40,000 at In 250V AC cos φ = 0.6	125	850
Socket-outlets	IEC 60884-1			1,25 In (100 position changes)	10,000 at In 250V AC cos φ = 0.8		
Latching relays	EN 60669-1 / EN 60669-2-2			1,25 In (200 position changes)	50,000 at In 250V AC cos φ = 0.6		
Momentary relays	EN 60669-1 / EN 60669-2-2						
Miniature circuit breakers	EN 60898-1			2** ÷ 5	3KA		
Residual current circuit breakers	EN 61009-1 / EN 61008-1	3KA	4,000				
Supports and plates	EN 60669-1	-	-	-	-	70	650

* For rated voltages and currents, see the specifications in the single codes. ** The value of 2 MΩ refers to a special condition established by the Standards given alongside.

Terminal resistance to cable traction: > 50N
Device hold on support: > 0.6J

TERMINAL TIGHTENING CAPACITY			
Stranded wires		Solid wires	
Minimum 0.75 mm ²	Maximum 2 x 4 mm ²	Minimum 0.5 mm ²	Maximum 2 x 2.5 mm ²

Playbus

	FLUSH-MOUNTING BOXES	SUPPORTS	DEVICES
3M	 GW 24 403  GW 24 403 PM	 GW 32 402  GW 32 403	  
4M	 GW 24 404  GW 24 404 PM	 GW 32 404	 
6M	 GW 24 406  GW 24 406 PM	 GW 32 406	
4+4M	 GW 24 237  GW 24 237 PM	 GW 32 407	 
6+6M	 GW 24 238	 GW 32 408	 
6+6+6M	 GW 24 239	 GW 32 409	  
2M		 GW 32 402	

PLATES

PLAYBUS YOUNG



GW 32 xx2

PLAYBUS YOUNG



GW 32 xx3

PLAYBUS



GW 32 xx2

PLAYBUS



GW 32 xx3

IP55 Watertight self-supporting plates



GW 32 461 - GW 32 462

PLAYBUS YOUNG



GW 32 xx4

PLAYBUS



GW 32 xx4

IP55 Watertight self-supporting plates



GW 32 466 - GW 32 467

PLAYBUS YOUNG



GW 32 xx6

PLAYBUS



GW 32 xx6

PLAYBUS



GW 32 xx7

PLAYBUS



GW 32 xx8

PLAYBUS



GW 32 009

PLAYBUS YOUNG



GW 32 xx2

PLAYBUS



GW 32 xx2