

44 MS - TRAILING AND MODULAR TERMINAL BLOCKS

**GWT
850°C**



TRAILING TERMINALS BLOCKS



GW 44 665

MOBILE TERMINAL BLOCKS WITH MODULAR BUSBARS - 450V - T 85°C - TRANSPARENT - IP20

Code	Max. section flex. cables	Min. section flex. cables	No. poles per bar	Pack Carton
Type of screw: Slotted				
GW 44 661	2.5 mm ²	1 mm ²	10	10/450
GW 44 665	4 mm ²	1.5 mm ²	10	10/450
GW 44 662	6 mm ²	2.5 mm ²	10	10/450
GW 44 663	10 mm ²	4 mm ²	10	10/300
GW 44 664	16 mm ²	6 mm ²	5	10/240
Type of screw: Socket head 5mm				
GW 44 666	25 mm ²	10 mm ²	1	5/150
GW 44 667	35 mm ²	16 mm ²	1	5/150

CHARACTERISTICS: GW44666 and GW44667 supplied in single terminals.

MODULAR TERMINAL BLOCKS




GW 44 601

POLYMER 12 POLE MODULAR TERMINAL BLOCKS WITH BRASS TERMINALS - 450V - T 85°C - BLACK

Code	Max. section flex. cables	Min. section flex. cables	hole Ø	Max load	Outer dim. LxHxD (mm)	Fixing	Pack Carton
GW 44 601	2.5 mm ²	0.75 mm ²	2.9 mm	24 A	95x15x16	With screw	10/480
GW 44 602	4 mm ²	1.5 mm ²	3.4 mm	32 A	117x17x20	With screw	10/240
GW 44 603	10 mm ²	4 mm ²	4.4 mm	57 A	141x20x23	With screw	10/160
GW 44 604	16 mm ²	6 mm ²	5.8 mm	76 A	172x25x32	With screw	10/120
GW 44 605	25 mm ²	10 mm ²	7.4 mm	101 A	210x34x38	With screw	3/36

44 MM - MULTI-POLE TERMINAL BLOCKS

**GWT
850°C**



PRESS-ON FIXING



GW 44 608

PRESS-ON MULTI-POLE TERMINAL BLOCKS - 450 V - GREY RAL 7035

Code	Connecting capacity	Pack Carton
GW 44 606	3 holes x 4 mm ²	10/100
GW 44 607	4 holes x 4 mm ²	10/100
GW 44 608	5 holes x 4 mm ²	10/100

NOTES: press-on fixing on 44 CE range boxes. (see "Selection Guide" synoptic table).