



GW 48 018

**HIGH RESISTANCE SHOCKPROOF PLAIN LIDS FOR PT / PT DIN AND PT DIN GREEN WALL BOXES
WHITE RAL 9016 - IP40**



Code	Suitable for	Shock resistance	Pack Carton
GW 48 013	GW48001	IK10	10/120
GW 48 014	GW48002 - GW48003	IK10	10/100
GW 48 015	GW48004	IK10	10/100
GW 48 016	GW48005	IK10	10/100
GW 48 017	GW48006 and GW48006PM	IK10	10/100
GW 48 018	GW48007 and GW48007PM	IK10	10/80
GW 48 019	GW48008 and GW48008PM	IK10	10/40
GW 48 020	GW48009 and GW48009PM	IK10	10/40
GW 48 021	GW48010	IK10	10/30
GW 48 022	GW48011	IK10	10/20

CHARACTERISTICS: surface embossing of the covers to facilitate painting. GWT 850 °C according to EN 60695-2-11.



GW 48 084

DEEP LIDS FOR PT / PT DIN AND PT DIN GREEN WALL BOXES - WHITE RAL 9016 - IP40



Code	Suitable for	Pack Carton
GW 48 084	GW48004	1/10
GW 48 085	GW48005	1/8
GW 48 086	GW48006 and GW48006PM	1/10
GW 48 087	GW48007 and GW48007PM	1/5
GW 48 088	GW48008 and GW48008PM	1/5

CHARACTERISTICS: the deep lids are ideal for passing from an exposed system to a chased one. They have a removable front plate and a frame for connecting with trunking. GWT 850 °C secondo EN 60695-2-11; max lid H = 66mm for boxes up to 392x152 and conduits with max Ø = 32mm.



GW 48 023

LONG SELF-TAPPING SCREWS FOR SECURING COVER

Code	Dimensions (mm)	Suitable for	Pack Carton
GW 48 023	Ø3x38	Junction boxes range 48 PT / PT DIN and PT DIN GREEN WALL	300/4200