

## PROTECTION

### DISCONNECTABLE FUSE-HOLDERS



GW 96 312

#### DISCONNECTABLE FUSE-HOLDERS



Code	Rated current	Fuse dimension (mm)	No. of modules EN 50022	Rated voltage	Pack Carton
<b>No. of poles: 1P</b>					
GW 96 206	20 A	8.5x31.5	1	400 V ac	12
GW 96 226	20 A	10.3x38	1	1000 V dc	12
GW 96 205	32 A	10.3x38	1	690 V ac	12
GW 96 207	50 A	14x51	1.5	690 V ac	12
<b>No. of poles: 1P+N</b>					
GW 96 216	20 A	8.5x31.5	2	400 V ac	6
GW 96 220	32 A	10.3x38	1	690 V ac	12
GW 96 215	32 A	10.3x38	2	690 V ac	6
GW 96 217	50 A	14x51	3	690 V ac	6
GW 96 218	100 A	22x58	4	690 V ac	2
<b>No. of poles: 2P</b>					
GW 96 301	20 A	8.5x31.5	2	400 V ac	6
GW 96 227	20 A	10.3x38	2	1000 V dc	6
GW 96 302	32 A	10.3x38	2	690 V ac	6
GW 96 303	50 A	14x51	3	690 V ac	6
<b>No. of poles: 3P</b>					
GW 96 306	20 A	8.5x31.5	3	400 V ac	4
GW 96 307	32 A	10.3x38	3	690 V ac	4
GW 96 308	50 A	14x51	4.5	690 V ac	4
<b>No. of poles: 3P+N</b>					
GW 96 311	20 A	8.5x31.5	4	400 V ac	3
GW 96 312	32 A	10.3x38	4	690 V ac	3
GW 96 313	50 A	14x51	6	690 V ac	3
GW 96 314	100 A	22x58	8	690 V ac	1

**APPLICATIONS:** protection against low voltage overcurrents in industrial and advanced tertiary application in case of high short-circuit currents.

**NOTES:** the products GW96226 and GW96227 are suitable for the protection and isolation of the photovoltaic strings too (Utilization category DC20B)

### FUSES



GW 72 105

#### CYLINDRICAL FUSES - TYPE GG

Code	Rated current	Rated voltage AC	Breaking capacity AC	Pack Carton
<b>Dimensions (mm): Ø 8.5 x 31.5</b>				
GW 72 111	2 A	400 V	50 kA	10/100
GW 72 112	4 A	400 V	50 kA	10/100
GW 72 113	6 A	400 V	50 kA	10/100
GW 72 114	10 A	400 V	50 kA	10/100
GW 72 115	16 A	400 V	50 kA	10/100
GW 72 116	20 A	400 V	50 kA	10/100
GW 72 117	25 A	400 V	50 kA	10/100
<b>Dimensions (mm): Ø 10.3 x 38</b>				
GW 72 104	2 A	500 V	120 kA	10/100
GW 72 105	6 A	500 V	120 kA	10/100
GW 72 107	10 A	500 V	120 kA	10/100
GW 72 101	16 A	500 V	120 kA	10/100
GW 72 108	20 A	500 V	120 kA	10/100
GW 72 109	25 A	500 V	120 kA	10/100
GW 72 110	32 A	400 V	120 kA	10/100
<b>Dimensions (mm): Ø 14 x 51</b>				
GW 72 121	25 A	690 V	80 kA	10/100
GW 72 122	32 A	500 V	80 kA	10/100
GW 72 123	40 A	500 V	80 kA	10/100
GW 72 124	50 A	400 V	80 kA	10/100
<b>Dimensions (mm): Ø 22 x 58</b>				
GW 72 103	63 A	690 V	80 kA	10/30

**NOTE:** fast fuse type.