



GW 72 131

CYLINDRICAL FUSES - TYPE GPV

Code	Rated current	Rated voltage DC	Breaking capacity DC	Pack Carton
Dimensions (mm): Ø 10.3 x 38				
GW 72 131	6 A	1000 V	30 kA	10
GW 72 132	8 A	1000 V	30 kA	10
GW 72 133	10 A	1000 V	30 kA	10
GW 72 134	12 A	1000 V	30 kA	10
GW 72 135	16 A	1000 V	30 kA	10
GW 72 136	20 A	1000 V	30 kA	10

APPLICATIONS: photovoltaic systems.

MOTOR PROTECTION SWITCHES



GW 96 758

MOTOR PROTECTION SWITCHES

Code	Operating current	Rated voltage (V)	No. of modules EN 50022	Pack Carton
No. of poles: 3P				
GW 96 751	0.1-0.16 A	230/400 ac	3	1/4
GW 96 752	0.16-0.25 A	230/400 ac	3	1/4
GW 96 753	0.25-0.4 A	230/400 ac	3	1/4
GW 96 754	0.4-0.63 A	230/400 ac	3	1/4
GW 96 755	0.63-1 A	230/400 ac	3	1/4
GW 96 756	1-1.6 A	230/400 ac	3	1/4
GW 96 757	1.6-2.5 A	230/400 ac	3	1/4
GW 96 758	2.5-4 A	230/400 ac	3	1/4
GW 96 759	4-6.3 A	230/400 ac	3	1/4
GW 96 760	6.3-10 A	230/400 ac	3	1/4
GW 96 761	10-16 A	230/400 ac	3	1/4
GW 96 762	16-25 A	230/400 ac	3	1/4
GW 96 763	25-40 A	230/400 ac	3	1/4

APPLICATIONS: protection of electric motors both in single-phase and 3-phase distribution. Using an adjustment screw, it is possible to set the thermal tripping threshold within an adjustable value range with a ratio of 1:1.6.

ACCESSORIES FOR MOTOR PROTECTION SWITCHES



GW 96 765

AUXILIARY CONTACTS FOR MOTOR PROTECTION SWITCHES

Code	Contacts Description	No. of contacts	Type of contacts	No. of modules EN 50022	Pack Carton
GW 96 764	Position	2	1 NO + 1 NC	0.5	1/12
GW 96 765	Fault/position indicator	2	CHANGE-OVER	0.5	1/12



GW 96 767

SHUNT TRIP RELEASE FOR MOTOR PROTECTION SWITCHES

Code	Rated voltage (V)	No. of modules EN 50022	Pack Carton
GW 96 767	110-415 ac	1	1/6