Colour	MOMENTARY ROUND PUSH-BUTTONS					
Colour	With	ı guard	Witho	ut guard	With backlit guard	
Green	GW 74 301		GW 74 313		GW 74 341	
Black	GW 74 302		GW 74 312		-	
White	GW 74 303		GW 74 314		GW 74 342	
Red	GW 74 304		GW 74 311		GW 74 343	
Blue	GW 74 305		GW 74 315		GW 74 344	
Yellow	GW 74 306		GW 74 316		GW 74 345	

Colour	ROUND MUSHROOM-HEAD PUSH-BUTTONS - Ø 40 MM				
Colour	With h	nolding	Without holding		
Dad	GW 74 364		GW 74 363		
Red	GW 74 367		GW 74 366		

Colour	ROUND MUSHROOM-HEAD EMERGENCY PUSH-BUTTONS - Ø 40 MM				
Colour	With h	olding	With hold	ing and key	
Dad	GW 74 361		CW74.2C2		
Red	GW 74 365		GW 74 362		

In bold, the illuminated versions

Positions	ROUND SELECTORS					
Pusitions	Lever type with	fixed positions	Extractable key with fixed position		Lever type with return	
0 - 1	GW 74 401		GW 74 411		GW 74 421	
1-0-2	GW 74 402		GW 74 412	((3)));	GW 74 422	

C -1	LUMINOUS	S INDICATORS
Colour	Direct p	ower supply
Green	GW 74 451	400
Red	GW 74 452	
Yellow	GW 74 453	
Light blue	GW 74 454	
White	GW 74 455	

COMPLEMENTARY ITEMS			
Type Contact			
Cinala santant	1 NO	GW 74 501	
Single contact	1 NC	GW 74 502	
	2 NO	GW 74 503	
Dual contact	2 NC	GW 74 505	
	1 NO + 1 NC	GW 74 504	
Lamp-holder - BA9S coupling		GW 74 511	

			COMPLETE CONTAINE	TE CONTAINERS			
Indicator lights Ø 22	With	guard	No. gangs	Contacts	Dimensions (LxHxD) mm		
Generic (black)	GW 27 201		1	1NO	66x82x65		
Emergency (red)	GW 27 202		1	1 NO 1 NC	66x82x65		
Start (green)	CW 27 202	* ***	* 100	*115	2	1 NO 1 NC	132x82x65
Stop (red)	· GW 27 203		2	INOTINE	152X62X65		
Start (green)							
Stop (red)	GW 27 204		3	1 NO 1 NC	66x171x65		
Signalling (white)							


	EMPTY CONTAINERS				
No. gangs	Cod	e	Side entries	Top / Bottom entries	Dimensions (LxHxD) mm
1	GW 27 101		2 x Ø 23	2 x Ø 23	66x82x65
1	GW 27 111 (*)	Street, and the	2 x Ø 23	2 x Ø 23	66x82x65
2	GW 27 102	7	6 x Ø 23	2 x Ø 23	132x82x65
3	GW 27 103		4 x Ø 23	2 x Ø 23	66x171x65
6	GW 27 104		4 x Ø 23	6 x Ø 23	132x171x65
12	GW 27 105		4 x Ø 23	6 x Ø 23	264x171x65

(*) GW 27 111: yellow lid and grey back-mounting box - Specific for emergency push-buttons. For all illuminated versions, the LED lamp must be purchased separately: GW 74 515 (12V); GW 74 516 (24V); GW 74 517 (110V); GW 74 518 (230V).

74 PS

Push-buttons, selectors and indicators Ø 22mm

The 74 PS range is a system of push-buttons, selectors and indicators (diameter 22 mm) with a degree of protection of IP66 for creating a real interface between man and machine, whilst at the same time controlling the operating status of the drives and equipment to ensure the highest safety standards.





Technical characteristics page 1070

OPERATORS Ø 22 MM - IP66

INSTALLATION





MOMENTARY PUSH-BUTTONS



GW 74 301

MUMENIARY	PO2H-ROI	IUNS WITH	KUUND GUAKD

Code	Colour	Pack
		Carton
GW 74 301	Green	10/60
GW 74 302	Black	10/60
GW 74 303	White	10/60
GW 74 304	Red	10/60
GW 74 305	Blue	10/60
GW 74 306	Yellow	10/60

APPLICATION: suitable for avoiding accidental activation, e.g.: gates, tool machines, etc..

SUPPLIED: 3-seat flange (2 of which are contact-holders).

 $\textbf{CHARACTERISTICS:} \ Also \ compatible \ with \ the \ water tight \ emergency \ enclosure \ GW42204 \ and \ GW42207.$



GW 74 311

MOMENTARY PUSH-BUTTONS WITHOUT ROUND GUARD

Code	Colour	Pack Carton
GW 74 311	Red	10/60
GW 74 312	Black	10/60
GW 74 313	Green	10/60
GW 74 314	White	10/60
GW 74 315	Blue	10/60
GW 74 316	Yellow	10/60

SUPPLIED: 3-seat flange (2 of which are contact-holders).

CHARACTERISTICS: Also compatible with the watertight emergency enclosure GW42204 and GW42207.



GW 74 345

MOMENTARY PUSH-BUTTONS WITH BACKLIT ROUND GUARD

Code	Colour	Pack
		Carton
GW 74 341	Green	10/60
GW 74 342	White	10/60
GW 74 343	Red	10/60
GW 74 344	Blue	10/60
GW 74 345	Yellow	10/60

APPLICATION: ideal for viewing the user operating status without the need for additional indicator lamps.

SUPPLIED: 3-seat flange (2 of which are contact-holders).

CHARACTERISTICS: can be combined with the lamp-holder GW74511 + LED lamp. Also compatible with the watertight emergency enclosure GW42204 and GW42207.



Dimension tables

INDICATORS 23.1 23.1 PUSH Ф23.4 30 26.9 26.9 19 30 GW 74 301 ÷ GW 74 306 GW 74 311 ÷ GW 74 316 23.1 23.1 45.8 26.9 19 30 26.9 20.6 30 GW 74 341 ÷ GW 74 345 GW 74 363 - GW 74 364 GW 74 366 - GW 74 367

Dimension tables

