

Modular accessories

90 AM

MODULAR ACCESSORIES





GW 96 012

SHUNT TRIP RELEASES

Code	Rated voltage (V)	No. of modules EN 50022	Pack Carton
GW 96 011	12-48 ac/dc	1	1/8
GW 96 012	110-125 dc 110-415 ac	1	1/8

APPLICATIONS: used for the remote trip of the coupled circuit breaker.

CHARACTERISTICS: minimum operating voltage: 0.7 Vn min. Maximum operating voltage: 1.1 Vn max.

NOTE: up to max. one release (shunt trip or under voltage) can be fitted to each circuit breaker with an auxiliary contact.



GW 96 016

UNDER VOLTAGE RELEASES (DELAYED)

Code	Rated voltage (V)	No. of modules EN 50022	Pack Carton
GW 96 016	230 ac	1	1/8
GW 96 017	24 ac/dc	1	1/8
GW 96 018	48 ac/dc	1	1/8

APPLICATIONS: constantly controls the effective value of the voltage, and trips the coupled circuit breaker when the voltage falls below its minimum value.

The 300 ms delay allows any tiny blackouts to be avoided, preventing the untimely tripping of circuit breaker.

NOTE: up to max. one release (shunt trip or under voltage) can be fitted to each circuit breaker with an auxiliary contact.

ACCESSORIES FOR CIRCUIT BREAKERS MTC / MT / MTHP / MDC



GW 96 022

SEALABLE SCREW CAPS

Code	Suitable for	Nr. pieces per module	Pack Carton
GW 96 022	MTC/MT/MDC	2	10/100
GW 96 026	MTHP/BDHP	1	10/100

APPLICATIONS: allows for sealing of terminal screws, preventing access to cable connections.



GW 96 042

POLE SEPARATOR

Code	Suitable for	Pack Carton
GW 96 042	MT/MDC	10/100