


**SURGE PROTECTIVE DEVICES LST**



GW D6 405

**SURGE PROTECTIVE DEVICES TYPE 1+2**




Code	Impulse current	Maximum discharge current	Rated voltage AC	No. of modules EN 50022	Aux end-of-life contact	Pack Carton
<b>No. of poles: 1P+N</b>						
GW D6 401	12.5 kA	65 kA	230 V	2	No	1
GW D6 404	25 kA	100 kA	230 V	4	Yes	1
<b>No. of poles: 3P+N</b>						
GW D6 402	12.5 kA	65 kA	400 V	4	No	1
GW D6 405	25 kA	100 kA	400 V	8	Yes	1

CHARACTERISTICS: SPDs are equipped with extractable cartridges with optic end-of-life signal.



GW D6 420

**SURGE PROTECTIVE DEVICES TYPE 2**



Code	Maximum discharge current	Rated voltage AC	No. of modules EN 50022	Aux end-of-life contact	Pack Carton
<b>No. of poles: 1P</b>					
GW D6 411	40 kA	230 V	1	No	1
GW D6 412	40 kA	230 V	1	Yes	1
GW D6 413	40 kA	400 V	1	No	1
<b>No. of poles: 1P+N</b>					
GW D6 407	20 kA	230 V	2	No	1
GW D6 417	40 kA	230 V	2	No	1
GW D6 418	40 kA	230 V	2	Yes	1
<b>No. of poles: 3P+N</b>					
GW D6 409	20 kA	400 V	4	No	1
GW D6 419	40 kA	400 V	4	No	1
GW D6 420	40 kA	400 V	4	Yes	1

CHARACTERISTICS: SPDs are equipped with extractable cartridges with optic end-of-life signal.



GW D6 426

**SURGE PROTECTIVE DEVICES TYPE 2 FOR PHOTOVOLTAIC APPLICATIONS**



Code	Maximum discharge current	Rated voltage DC	No. of modules EN 50022	Aux end-of-life contact	Pack Carton
GW D6 426	40 kA	600 V	3	No	1
GW D6 428	40 kA	1000 V	3	No	1

CHARACTERISTICS: SPDs are equipped with extractable cartridges with optic end-of-life signal.



GW D6 430

**SURGE PROTECTIVE DEVICES FOR TELECOM AND DATALINE**



Code	Maximum discharge current	Rated voltage AC	No. of modules EN 50022	Aux end-of-life contact	Pack Carton
GW D6 430	10 kA	50 V	1	No	1